



**Product:** [8917](#)

Lead Wire, #16 Str TC, PVC Ins, AWM 1015 AWM 1230

[Request Sample](#)

**Product Description**

Low Temp Plastic Lead Wire, 16AWG (26x30) Tinned Copper, PVC Insulation, AWM 1015 AWM 1230 CSA TYPE TEW JQA-F 600V 105C

**Technical Specifications**

**Product Overview**

Suitable Applications:	inter-connection circuits, internal wiring of computer and electronic equipments, internal wiring of appliances, machine tool wire
------------------------	--

**Construction Details**

**Conductor**

AWG	Stranding	Material
16	26x30	TC - Tinned Copper

**Insulation**

Material	Thickness	Nom. Insulation Diameter
PVC - Polyvinyl Chloride	0.032 in	0.123

Cable Diameter (Nominal):	0.123 in
---------------------------	----------

**Electrical Characteristics**

**Electricals**

Nom. Conductor DCR	Max. Current
4.0 Ohm/1000ft	Single conductor in free air @ 30°C: 26 A

**Voltage**

UL Voltage Rating
600 V RMS

**Mechanical Characteristics**

**Temperature**

UL Rating	Operating
105°C	-30°C To +105°C

**Bend Radius**

Stationary Min.
0.5 in

Bulk Cable Weight:	13.75 lbs/1000ft
--------------------	------------------

**Standards and Compliance**

Sustainability:	CA Prop 65
Flammability / Fire Resistance:	VW-1, FT1
NEC / UL Compliance:	Article 310, MTW
AWM Compliance:	UL AWM Styles 1015, 1230, CSA AWM I A/B
CEC / C(UL) Compliance:	TEW

European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

**History**

Update and Revision:	Revision Number: 0.332 Revision Date: 11-17-2020
----------------------	--

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.