



■ Features :

- 1500VDC I/O isolation
- 3000VDC I/O isolation(optional)
- Operating temperature range of -40 ~ +85°C without derating
- Internal SMD technology
- Built-in EMI filter
- Cooling by free air convection
- Non-conductive plastic case
- Dual in line package
- Industry standard pinout
- 100% burn-in test
- Low cost / High reliability
- 2 years warranty



SELECTION GUIDE



ORDER NO.	SMA01L-05	SMA01M-05	SMA01N-05	SMA01L-09	SMA01M-09	SMA01N-09
DC OUTPUT VOLTAGE	5V			9V		
OUTPUT CURRENT RANGE	0 ~ 200mA			0 ~ 110mA		
EFFICIENCY(Typ.)	77%	79%	77%	77%	78%	75%
ORDER NO.	SMA01L-12	SMA01M-12	SMA01N-12	SMA01L-15	SMA01M-15	SMA01N-15
DC OUTPUT VOLTAGE	12V			15V		
OUTPUT CURRENT RANGE	0 ~ 84mA			0 ~ 67mA		
EFFICIENCY(Typ.)	78%	80%	78%	79%	79%	77%

SPECIFICATION

OUTPUT	RATED POWER	1W				
	RIPPLE & NOISE (max.) Note.2	100mVp-p				
	LINE REGULATION Note.3	±1.2% for 1% input variation				
	LOAD REGULATION Note.4	±8.0%				
	VOLTAGE ACCURACY	±2.0%				
INPUT	SWITCHING FREQUENCY(Typ.)	100KHz				
	VOLTAGE RANGE	4.5 ~ 5.5V	10.8 ~ 13.2V	21.6 ~ 26.4V	4.5 ~ 5.5V	10.8 ~ 13.2V
	NORMAL VOLTAGE	5V	12V	24V	5V	12V
	INPUT CURRENT	Full load	265mA	110mA	57mA	110mA
		No load	32mA	15mA	11mA	11mA
PROTECTION	PROTECTION (FUSE RECOMMENDED)	500mA	250mA	150mA	500mA	250mA
	FILTER	Capacitor type				
	OVERLOAD	Momentary				
		Protection type : Broken				
ENVIRONMENT	SHORT CIRCUIT	Momentary				
		Protection type : Broken				
	WORKING TEMP.	-40 ~ +90°C (Refer to "Derating Curve")				
	WORKING HUMIDITY	20% ~ 90% RH non-condensing				
	STORAGE TEMP., HUMIDITY	-55 ~ +125°C, 10 ~ 95% RH				
SAFETY & EMC	TEMP. COEFFICIENT	±0.05% / °C (0 ~ 50°C)				
	VIBRATION	10 ~ 500Hz, 2G 10min./1 cycle, period for 60min. each along X, Y, Z axes				
	SAFETY STANDARDS	EAC TP TC 004 approved				
	WITHSTAND VOLTAGE	I/P-O/P:1.5KVDC				
ISOLATION RESISTANCE	ISOLATION RESISTANCE	I/P-O/P: 100M Ohms / 500VDC / 25°C / 70% RH				
	ISOLATION CAPACITANCE	80pF max.				
	EMI RADIATION	Compliance to EN55032 Class B, FCC part 15 Class B, EAC TP TC 020				
OTHERS	EMS IMMUNITY	Compliance to EN61000-4-2,3,4,5,6,8 light industry level, criteria A, EAC TP TC 020				
	MTBF	700khrs min. MIL-HDBK-217F(25°C)				
	DIMENSION (L*W*H)	12.7*10.16*7.1mm or 0.50**0.40**0.28" inch for 5V,12V input ; 12.7*10.16*7.62mm or 0.50**0.40**0.30" inch for 24V input				
	WEIGHT	1.7g				

■ Mechanical Specification


Unit: mm (inch)



■ Pin Configuration

Pin No.	Output
1	-Vin
4	+Vin
5	+Vout
7	-Vout

■ Derating Curve



NOTE

1. All parameters are specified at normal input, rated load, 25°C 70% RH ambient.
2. Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.
3. Line regulation is measured from low line to high line at rated load.
4. Load regulation is measured from 20% to 100% rated load.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[MEAN WELL](#):

[SMA01L-15](#) [SMA01M-05](#) [SMA01M-09](#) [SMA01M-12](#) [SMA01M-15](#) [SMA01N-12](#)