

Feed-through connector - P-FIX - 3038956

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Feed-through connector, Length: 10.5 mm, Width: 4 mm, Color: gray

Product Features

- Can be used in all ...-TG disconnect terminal blocks from the CLIPLINE complete system
- The P-FIX contact metal seals the disconnect point with the same shape and cannot be removed again once fitted



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
Weight per Piece (excluding packing)	0.472 g
Custom tariff number	85389099
Country of origin	Poland

Technical data

Dimensions

Length	10.5 mm
Width	4 mm

General

Color	gray
-------	------

Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	V0

Feed-through connector - P-FIX - 3038956

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27141190
eCl@ss 9.0	27141190

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002848
ETIM 5.0	EC002848

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

Approvals

Approvals

Approvals

CSA / EAC


Ex Approvals

Approvals submitted

Approval details

Feed-through connector - P-FIX - 3038956

Approvals

CSA 	
Nominal current IN	15 A
EAC	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

3038956