

## Specification Sheet

Part Number: CT2012X2



Self-Laminating Tag, Caution Write-On, Telephone Cable, 3.5" x 2.0", Yellow, 25/pkg

Article Number	597-00031
----------------	-----------

Type	CT2012
------	--------

Color	Yellow (YE)
-------	-------------

Features & Benefits	<ul style="list-style-type: none"><li>• Clear laminating plastic flap permanently protects the writing and data marked on the tag.</li><li>• Mounting holes for easy mounting using standard cable ties.</li><li>• Markers can be mounted in any direction, either vertically, horizontally, as a wrap-around identification plate or as a flag for the best visual position on the cable assembly.</li></ul>
---------------------	---

Quantity Per	pack
--------------	------

<b>Product Description</b>	HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease. <b>Product Features/bold</b> - Easily and conveniently fits in a pants or shirt pocket. - Once loaded, unit allows minimal label exposure to dust and moisture. - Can be used with standard ball point pens or HellermannTyton nylon marking pens. - Excess liner is easily cut-off by tearing it over the edge guide at the front of the unit. - The dispenser can be reloaded over and over again, making it a cost-effective and efficient method of labeling.
<b>Short Description</b>	Self-Laminating Tag, Caution Write-On, Telephone Cable, 3.5" x 2.0", Yellow, 25/pkg
<b>Global Part Name</b>	CT2012-PVC-YE
<b>Technical Description</b>	Caution Write-On Self-Laminating Tag, Telephone Cable, 3.5" X 2.0", Yellow
<b>Width W (Imperial)</b>	3.5
<b>Width W (Metric)</b>	88.9
<b>Height H (Imperial)</b>	1.5
<b>Height H (Metric)</b>	38.1
<b>Material</b>	Polyvinylchloride (PVC)
<b>Material Shortcut</b>	PVC

<b>Adhesive</b>	Acrylic
<b>Halogen Free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature</b>	-40°F to +257°F (-40°C to +125°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3926909988
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1
<b>Weight (Metric)</b>	0.22
<b>Weight (Imperial)</b>	0.5