AC & DC FAN TRAYS



UL and cUL Recognized

THERMALCARE FAN TRAYS

MODEL NUMBER	PART NUMBER	VOLTAGE	FANS	GFM
	AG FAN TRAY	s		
OA300S	FTA-03115-014(BK)		3	330
OA600S	FTA-06115-014(BK)		6	660
OA300	FTA-03115-018(BK)	115VAC	3	330
OA300-A	expansion module	TISVAC	3	330
OA600	FTA-06115-018(BK)		6	660
OA900	FTA-09115-018(BK)		9	990
OA302S	FTA-03220-014(BK)	100	3	330
OA602S	FTA-06220-014(BK)	230VAC	6	660
DA302	FTA-03220-018(BK)		3	330
OA302-A	expansion module		3	330
OA602	FTA-06220-018(BK)		6	660
OA902	FTA-09220-018(BK)		9	990
	DUAL VOLTAGE AC	TRAYS		
OA300S-DV	FTA-03DV-014(BK)		3	330
OA600S-DV	FTA-06DV-014(BK)	7	6	660
OA300-DV	FTA-03DV-018(BK)	115/230VAC	3	330
OA300DV-A	expansion module		3	330
OA600-DV	FTA-06DV-018(BK)		6	660
OA900-DV	FTA-09DV-018(BK)		9	990
	DG FAN TRAY	s		
OD300S-12	FTD-03012-014(BK)		3	330
OD600S-12	FTD-06012-014(BK)		6	660
OD300-12	FTD-03012-018(BK)	120/06	3	330
OD300-12-A	expansion module	12VDC	3	330
OD600-12	FTD-06012-018(BK)		6	660
OD900-12	FTD-09012-018(BK)		9	990
OD300S-24	FTD-03024-014(BK)	1	3	330
OD600S-24	FTD-06024-014(BK)	24VDC	6	660
OD300-24	FTD-03024-018(BK)		3	330
OD300-24-A	expansion module		3	330
OD600-24	FTD-06024-018(BK)		6	660
OD900-24	FTD-09024-018(BK)		9	990
DD300S-48	FTD-03048-014(BK)		3	330
OD300-48-A	expansion module	7	3	330
OD600S-48	FTD-06048-014(BK)	1	6	660
OD300-48	FTD-03048-018(BK)	48VDC	3	330
OD600-48	FTD-06048-018(BK)	1	6	660
OD900-48	FTD-09048-018(BK)		9	990


Fan trays are UL listed by the part number only. Model numbers are assigned as configuration descriptors only and do not affect UL certifications.



BASIC FAN TRAY SPECIFICATIONS ...

FRAME

Heavy Duty steel construction with extruded aluminum side rails. Black color standard, gray available by special order.



HARDWARE

EZ-mount clip nuts and fasteners

CONFIGURATION

Standard trays have 3, 6 or 9 fans installed. Our ADD-a-MODULE feature allows the user to easily increase or decrease the amount of cooling in 3-fan increments.

OPTIONS

Ultrashort 3-fan Tray available. Lighted on/off rocker switch. Dual voltage selector switch. Fan monitor and alarm. MEDIUM AND LOW SPEED FANS CAN BE SUBSTITUTED FOR LOW-NOISE APPLICATIONS. Ultra high speed fans are available.

We use only top quality, ball bearing ORION FANS in our fan tray assemblies. For DC applications plastic fans are standard however diecast aluminum fans can be substituted on request. (Minimums apply.)

We can customize our fan trays to perform virtually any function required. If you need something which does not appear in this catalog just let us know. Our sales engineers will be happy to discuss your needs and provide a solution.



MAXIMUM FLEXIBILITY



ADD-A-MODULE

POWER CONNECTION

AC trays have standard 115 or 230 VAC power cords. DC trays come with standard DC screw terminals.









Dual Voltage DC P

DC Power



ORION STANDARD

L=19" W=19" D=1.75" with IEC320, C14-type connector on back. 115/230 voltage selector included with dual voltage tray.




ORION SHORT TRAY

L=14" W=19" D=1.75". Optional lighted on/off rocker with IEC320, C14type connector on back. 115/230 voltage selector included with dual voltage tray.



EXPANSION MODULE Maximum flexibility - minimum effort. Add or subtract fan modules quickly and easily as your cooling needs change.



Standard trays are populated with high speed, ball bearing fans. We can substitute virtually any 120mm AC or DC fan for your special project. Just let your sales engineer know what your requirements are and he or she will be happy to provide a solution.

CUSTOM TRAYS

ORION FANS fan trays are available in dozens of stock configurations. If you cannot find what you are looking for give us a call. We can design and build your trays from scratch or we can help you come up with solutions for your toughest problems.




Dual Voltage Selector



Lighted on/off rocker



Warning Lights









Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Orion Fans:

OA300 OA602S OA300S-2TB OA302 OA302S OA300S OD300S-12 OD300S-24 OD300S-48 OA600S-ER-DV
OA300-2TB OA600S-DV OD900-48 OA600S OA902-18 OD300-48 OD600S-12 OD600S-24 OD600S-48
OA300S-DV OA900 OA300S7 OA300-DV OA600 OA600-DV OA602 OA900-DV OA902 OD300-12 OD300-24
OD600-12 OD600-24 OD600-48 OD900-12 OD900-24 OD600-48M OA300A OA302A OD300S7-24 OD300S748
W/TERMBLOCK OD300S7-24 W/TERMBLOCK OD300S-60