

Within Series Adaptor 34_SMA-50-0-51/199_N

Description

Bulkhead adaptor jack/jack
SMA jack (female) / SMA jack (female)



Interface standard
Series SMA - IEC 60169-15_MIL-STD-348A/310_CECC 22110

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	18 GHz
VSWR	DC - 18 GHz
	≤ 1.05 + 0.005 f (GHz)

Mechanical Data

Number of matings	500
Weight	0.0038 kg

Environmental Data

Operating temperature 2011/65/EU (RoHS)	-65 °C to 125 °C compliant
--	-------------------------------

Material Data

Interface - SMA jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	

Interface - SMA jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	

Related Documents

Catalogue drawing	DCA-00013642
Mounting hole	DOU-00008731

Ordering Information

Single package	34_SMA-50-0-51/199_NE
----------------	-----------------------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[34_SMA-50-0-51/199_NE](#)