



RECOMMENDED PC BOARD MOUNTING DIMENSIONS FOR .063[1.60] THICK PC BOARD AND .012[.305] STENCIL THICK

1. TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD.
2. THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
3. RETENTION FEATURES ON SOLDER TAILS, LOCATED AT MANUFACTURERS OPTION.
4. $\text{M} \text{ } \phi 0.51[.020]$ FOR KINKED TAILS.
5. HOUSING: LCP, COLOR-BLACK. POST: COPPER ALLOY.
6. 0.000127 [0.000005] GOLD IN CONTACT AREA, 0.00254-0.00508 [0.000100-.0000200] MATTE TIN-LEAD ON SOLDER TAIL, ALL OVER 0.00127 [0.000050] NICKEL.
7. 0.000127 [0.000005] GOLD IN CONTACT AREA, 0.00254-0.00508 [0.000100-.0000200] MATTE TIN ON SOLDER TAIL, ALL OVER 0.00127 [0.000050] NICKEL.
8. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER
7	101.19 [3.984]	99.06 [3.900]	39	80	9-146264-0
7	98.65 [3.884]	96.52 [3.800]	38	78	8-146264-9
7	96.11 [3.784]	93.98 [3.700]	37	76	8-146264-8
7	93.57 [3.684]	91.44 [3.600]	36	74	8-146264-7
7	91.03 [3.584]	88.90 [3.500]	35	72	8-146264-6
7	88.49 [3.484]	86.36 [3.400]	34	70	8-146264-5
7	85.95 [3.384]	83.82 [3.300]	33	68	8-146264-4
7	83.41 [3.284]	81.28 [3.200]	32	66	8-146264-3
7	80.87 [3.184]	78.74 [3.100]	31	64	8-146264-2
7	78.33 [3.084]	76.20 [3.000]	30	62	8-146264-1
7	75.79 [2.984]	73.66 [2.900]	29	60	8-146264-0
7	73.25 [2.884]	71.12 [2.800]	28	58	7-146264-9
7	70.71 [2.784]	68.58 [2.700]	27	56	7-146264-8
7	68.17 [2.684]	66.04 [2.600]	26	54	7-146264-7
7	65.63 [2.584]	63.5 [2.500]	25	52	7-146264-6
7	63.09 [2.484]	60.96 [2.400]	24	50	7-146264-5
7	60.55 [2.384]	58.42 [2.300]	23	48	7-146264-4
7	58.01 [2.284]	55.88 [2.200]	22	46	7-146264-3
7	55.47 [2.184]	53.34 [2.100]	21	44	7-146264-2
7	52.93 [2.084]	50.80 [2.000]	20	42	7-146264-1
7	50.39 [1.984]	48.26 [1.900]	19	40	7-146264-0
7	47.85 [1.884]	45.72 [1.800]	18	38	6-146264-9
7	45.31 [1.784]	43.18 [1.700]	17	36	6-146264-8
7	42.77 [1.684]	40.64 [1.600]	16	34	6-146264-7
7	40.23 [1.584]	38.10 [1.500]	15	32	6-146264-6
7	37.69 [1.484]	35.56 [1.400]	14	30	6-146264-5
7	35.15 [1.384]	33.02 [1.300]	13	28	6-146264-4
7	32.61 [1.284]	30.48 [1.200]	12	26	6-146264-3
7	30.07 [1.184]	27.94 [1.100]	11	24	6-146264-2
7	27.53 [1.084]	25.40 [1.000]	10	22	6-146264-1
7	24.99 [.984]	22.86 [.900]	9	20	6-146264-0
7	22.45 [.884]	20.32 [.800]	8	18	5-146264-9
7	19.91 [.784]	17.78 [.700]	7	16	5-146264-8
7	17.37 [.684]	15.24 [.600]	6	14	5-146264-7
7	14.83 [.584]	12.70 [.500]	5	12	5-146264-6
7	12.29 [.484]	10.16 [.400]	4	10	5-146264-5
7	9.75 [.384]	7.62 [.300]	3	8	5-146264-4
7	7.21 [.284]	5.08 [.200]	2	6	5-146264-3
7	4.67 [.184]	2.54 [.100]	1	4	5-146264-2
7	2.13 [-]	- [-]	-	2	5-146264-1
PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER

LOC	DIST	REVISED PER	ECO-	DATE	DN	APVD
AD	00	ECO-14-000255		15JUL2014	NK	MM

PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER
6	101.19 [3.984]	99.06 [3.900]	39	80	4-146264-0
6	98.65 [3.884]	96.52 [3.800]	38	78	3-146264-9
6	96.11 [3.784]	93.98 [3.700]	37	76	3-146264-8
6	93.57 [3.684]	91.44 [3.600]	36	74	3-146264-7
6	91.03 [3.584]	88.90 [3.500]	35	72	3-146264-6
6	88.49 [3.484]	86.36 [3.400]	34	70	3-146264-5
6	85.95 [3.384]	83.82 [3.300]	33	68	3-146264-4
6	83.41 [3.284]	81.28 [3.200]	32	66	3-146264-3
6	80.87 [3.184]	78.74 [3.100]	31	64	3-146264-2
6	78.33 [3.084]	76.20 [3.000]	30	62	3-146264-1
6	75.79 [2.984]	73.66 [2.900]	29	60	3-146264-0
6	73.25 [2.884]	71.12 [2.800]	28	58	2-146264-9
6	70.71 [2.784]	68.58 [2.700]	27	56	2-146264-8
6	68.17 [2.684]	66.04 [2.600]	26	54	2-146264-7
6	65.63 [2.584]	63.5 [2.500]	25	52	2-146264-6
6	63.09 [2.484]	60.96 [2.400]	24	50	2-146264-5
6	60.55 [2.384]	58.42 [2.300]	23	48	2-146264-4
6	58.01 [2.284]	55.88 [2.200]	22	46	2-146264-3
6	55.47 [2.184]	53.34 [2.100]	21	44	2-146264-2
6	52.93 [2.084]	50.80 [2.000]	20	42	2-146264-1
6	50.39 [1.984]	48.26 [1.900]	19	40	2-146264-0
6	47.85 [1.884]	45.72 [1.800]	18	38	1-146264-9
6	45.31 [1.784]	43.18 [1.700]	17	36	1-146264-8
6	42.77 [1.684]	40.64 [1.600]	16	34	1-146264-7
6	40.23 [1.584]	38.10 [1.500]	15	32	1-146264-6
6	37.69 [1.484]	35.56 [1.400]	14	30	1-146264-5
6	35.15 [1.384]	33.02 [1.300]	13	28	1-146264-4
6	32.61 [1.284]	30.48 [1.200]	12	26	1-146264-3
6	30.07 [1.184]	27.94 [1.100]	11	24	1-146264-2
6	27.53 [1.084]	25.40 [1.000]	10	22	1-146264-1
6	24.99 [.984]	22.86 [.900]	9	20	1-146264-0
6	22.45 [.884]	20.32 [.800]	8	18	1-146264-9
6	19.91 [.784]	17.78 [.700]	7	16	1-146264-8
6	17.37 [.684]	15.24 [.600]	6	14	1-146264-7
6	14.83 [.584]	12.70 [.500]	5	12	1-146264-6
6	12.29 [.484]	10.16 [.400]	4	10	1-146264-5
6	9.75 [.384]	7.62 [.300]	3	8	1-146264-4
6	7.21 [.284]	5.08 [.200]	2	6	1-146264-3
6	4.67 [.184]	2.54 [.100]	1	4	1-146264-2
6	2.13 [-]	- [-]	-	2	146264-1
PLATING	C	B	A	NO. OF POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIN T. HOFFMAN DBMAY95
 CHK G. DUBNICZKI 04MAR96
 APVD G. DUBNICZKI 04MAR96

NAME: HEADER ASSEMBLY, MOD II , BREAKAWAY, DOUBLE ROW, .100 X100 CL , VERTICAL, WITH RETENTION FEATURE, .025 SQ.POSTS, HIGH TEMPERATURE

PRODUCT SPEC: APPLICATION SPEC

SIZE: A1 CASE CODE: 00779 DRAWING NO: 146264 RESTRICTED TO: CUSTOMER DRAWING

SCALE: 4:1 SHEET: 1 OF 1 REV: H

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[6-146264-0](#)