

SPECIFICATION CONTROL DRAWING

55PC0221

TITLE

TWO CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, 600 VOLT

Date


10-19-05

Revision

D

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.

COMPONENT WIRES - 55PC0211



CONSTRUCTION DETAILS

| PART NUMBER 1/ | CONDUCTOR SIZE (AWG) | DIAMETER (in.) | | | WEIGHT (lb/1000 ft.) | |
|-------------------|----------------------------|---------------------|-----------------|---------------------|-------------------------|---------------------|
| | | LOWER SPEC LIMIT | TARGET VALUE | UPPER SPEC LIMIT | TARGET VALUE | UPPER SPEC LIMIT |
| 55PC0221-24-* | 24 | .076 | .079 | .082 | 4.00 | 4.23 |
| 55PC0221-22-* | 22 | .088 | .091 | .094 | 5.87 | 6.12 |
| 55PC0221-20-* | 20 | .105 | .108 | .111 | 8.87 | 9.17 |
| 55PC0221-18-* | 18 | .124 | .127 | .130 | 13.33 | 13.82 |
| 55PC0221-16-* | 16 | .139 | .142 | .145 | 16.94 | 17.46 |
| 55PC0221-14-* | 14 | .168 | .172 | .176 | 26.07 | 26.78 |
| 55PC0221-12-* | 12 | .205 | .209 | .214 | 39.93 | 40.85 |
| 55PC0221-10-* | 10 | .252 | .258 | .264 | 62.99 | 64.65 |
| 55PC0221- 8-* | 8 | .376 | .392 | .406 | 115. | 120. |

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 150°C

Maximum continous conductor temperature

VOLTAGE RATING: 600 volts (rms) at sea level

INSULATION FLAWS:

Impulse Dielectric Test, 8.0 kV (peak)

PART NUMBER:

The "*" in the part numbers above shall be replaced by a color code designator with a slash separating the component wire colors.

1/ Example: AWG 22, black and red component wires;
55PC0221-22-0/2

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx"). OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

tyco
Electronics

Raychem Wire & Cable
501 Oakside Avenue
Redwood City, CA 94063-3800
Phone: 1-800-227-8816
Fax: 1-650-361-6297

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[55PC0221-12-9/96](#)