



Marquardt Mechatronik GmbH
Schloss-Str. 16
78604 Rietheim-Weilheim
Germany

Phone: +49 (0) 7424 / 99-0
Fax: +49 (0) 7424 / 99-2399
Net: www.marquardt.de
E-mail: marquardt@marquardt.de

Technical data

Product image / Drawings

Product number

3251.0004

Actuator color / printing



Product family

Rocker switches

Actuation type

direct

ROHS conform

yes

Product code

3250-3B-19-1-0-B0-bl-1390-1380-00

Switching function

Changeover switch with OFF-position
in the center (2xSPST - Center OFF)

Material fixed contact

AgNi

Number of poles

2 x 1 - pole

connections

Quick-connect terminal, 3.0 x 0.8

Mechanical life endurance

50E4

Rating IEC

10 (5) A 12 V DC 1E5

Contact resistance (new condition)

< 100 (1 A 12 V DC) mOhm

Insulation resistance (new condition)

> 100 (500 V DC) MOhm

Proof tracking

250 PTI

Protection type

Connection IP 40
Actuator IP 66 and IP 67

Ambient temperature

-40 °C ... +85 °C

Ambient temperature

-40 °C ... +85 °C

Actuators and additional actuators

rocker: PC, transparent white, black
varnished, lasered symbol

Housing description

housing: PP, black
base plate: PA, black



Connection surface	bearing connection external connection	silver plated silver plated
Contact material	AgNi	
Lighting	Symbol position 1 + 2: LED, 12 V, green	
Operating force	7 N to 12 N +1,5 N	
Miscellaneous	circuit symbol: 50.108 / momentary function both sides	
Additional labeling	50.108	
Type of fastening	Snap fastening	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Marquardt:](#)

[3251.0004](#)