

4		3		2		1					
THIS DRAWING IS UNPUBLISHED.				RELEASED FOR PUBLICATION							
© COPYRIGHT - By -				ALL RIGHTS RESERVED.							
LOC G		DIST 14		REVISIONS							
P		LTR		DESCRIPTION		DATE	DWN	APVD			
		M3		REVISED PER ECO-11-004820		11MAR11	RK	HMR			
AMP WIRE RANGE		UL Listed FILE E13288		SR LR7189 Certified							
16-14 AWG SOLID OR STRANDED		16-14 AWG SOLID OR STRANDED		16-14 AWG SOLID OR STRANDED							
<div>SERRATIONS</div> <div>WIRE STOP</div> <div>INSULATION</div> <div>BODY</div> <div>AMP</div> <div>AMP</div> <div>AMP</div> <div>A</div> <div>27.05 MAX</div> <div>[1.065]</div> <div>STYLE 1</div>				<div>SERRATIONS</div> <div>WIRE STOP</div> <div>INSULATION</div> <div>BODY</div> <div>AMP</div> <div>AMP</div> <div>AMP</div> <div>AM</div> <div>28.07 MAX</div> <div>[1.105]</div> <div>STYLE 2</div>				<div>1. WIRE INSUL DIA, 2.92-4.32 [.115-.170]</div> <div>2 TAPE, NO STICKY</div>			
				<div>1</div> <div>50</div> <div>LOOSE PIECE, BAG</div> <div>8-34071-5</div>							
				<div>1</div> <div>5</div> <div>LOOSE PIECE, BLS</div> <div>8-34071-4</div>							
				<div>1</div> <div>100</div> <div>LOOSE PIECE, BOX</div> <div>8-34071-1</div>							
<div>2</div>				<div>2</div> <div>2500</div> <div>ON TAPE, REEL</div> <div>4-34071-4</div>							
				<div>2</div> <div>2500</div> <div>ON TAPE, REEL</div> <div>2-34071-3</div>							
				<div>2</div> <div>1000</div> <div>LOOSE PIECE</div> <div>2-34071-2</div>							
				<div>1</div> <div>2500</div> <div>ON TAPE, REEL</div> <div>2-34071-1</div>							
				<div>1</div> <div>1000</div> <div>LOOSE PIECE</div> <div>34071</div>							
				<div>STYLE</div> <div>QTY</div> <div>PACKAGE TYPE</div> <div>PART NO</div>							
AMP INCORPORATED CUSTOMER SERVICE SYSTEMS				MAX RECOMMENDED OPERATING TEMPERATURE: 90°C [194° F]							
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS		PRODUCT INFORMATION CENTER 1-800-522-6752		VOLTAGE RATING: 600V MAX (1000V FIXTURE OR SIGN)							
FOR APPLICATION TOOLING INFORMATION		TOOLING ASSISTANCE CENTER 1-800-722-1111		CIRCULAR MIL AREA: 1.04-2.62mm² [2,050-5,180] SOLID OR STRANDED							
FOR ORDER ENTRY		1-800-526-5142		THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.							
THIS DRAWING IS A CONTROLLED DOCUMENT.				DWN M ELLIS 19JUL95							
DIMENSIONS: mm [INCHES]				TOLERANCES UNLESS OTHERWISE SPECIFIED:							
				0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -							
MATERIAL				FINISH							
BODY, CU ASTM B 152 SLV, PVC, COLOR-BLUE				TIN PLATE ASTM B545							
DWN M ELLIS 19JUL95				CHK C PRESNELL 19JUL95							
APVD S BORTNER 19JUL95				NAME							
PRODUCT SPEC UL486A				SIZE CAGE CODE DRAWING NO RESTRICTED TO							
APPLICATION SPEC -				A3 00779 C-34071							
WEIGHT -				SCALE SHEET REV							
CUSTOMER DRAWING				4:1 1 OF 1 M3							

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-34071-1 \(Cut Strip\)](#)