

## UNCONTROLLED DOCUMENT

CAUTION: STATIC SENSITIVE DEVICE FOLLOW PROPER E.S.D. HANDLING PROCEDURES WHEN WORKING WITH THIS PART.





## PART NUMBER SSP-01TWB9WB12

E.C.N. NUMBER AND REVISION COMMENTS DATE E.C.N. #10897. 7.30.02

REV.

11.16.06

ELECTRO-OPTICAL CH	ARACTERISTICS	T <sub>A</sub> =25°C	V <sub>f</sub> =12	<u>I</u> V	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH				nm	
FORWARD VOLTAGE		12	14.0	$v_f$	
REVERSE VOLTAGE	5.0			٧ <sub>٢</sub>	ابر100µA
AXIAL INTENSITY		11000		mcd	$V_f = 12V$
VIEWING ANGLE		30		2x theta	
EMITTED COLOR:	ULTRA WHITE				
EPOXY LENS FINISH:	WATER CLEAR	LENS			

## LIMITS OF SAFE OPERATION AT 25°C PER DIE

REV.

В

E.C.N. #11148

PARAMETER	MAX	UNITS
PEAK FÖRWARD VOLTAGE	14	V
■ STEADY CURRENT	20	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	- 1.2	mW/°C
OPERATING, STORAGE TEMP.	- 40 TO +85	•c



UNCONTROLLED DOCUMENT

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.0010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECINAL PRECISION MAX.= +0.00 (±0.002), XXX=±0.127 (±0.005).

REV. PART NUMBER SSP-01TWB9WB12

LED MINIATURE WEDGE BASE LAMP, WHITE, WATER CLEAR LENS.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF SUNBRITE LEDS EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY SUNBRITE LEDS, THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND

SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THRO PARTIES.

RELIABILITY NOTE

DUR WANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FALURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



286 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.2867 WEB: www.sunbriteleds.com

DRAWN: JC

CHECKED: | APPROVED:

DATE: 11.16.06 PAGE: 1 OF 1

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSP-01TWB9WB12