

Data Sheet

RF TERMINATION Type 65_BNC-75-0-7/133_N

Description

Standard Termination, Low Power



Product Configuration

Connector	BNC plug (male)
Interface standards	IEC 60169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data	
Nominal Impedance	75 Ω
Frequency range	0 to 1 GHz
VSWR max.	1.22
Power rating	0.4 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature.
Mechanical Data	
Weight	0.01 kg
Environmental Data	
Operating temperature 2011/65/EU (RoHS)	-40 °C to 130 °C compliant

Material Data

Piece Part	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

Ordering Information

Single Packaging	65_BNC-75-0-7/133_NE
Packaging	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

[65_BNC-75-0-7/133_NE](#)