






REVISIONS					
#	LYR	DESCRIPTION	DATE	DWN	APVD
	D	REVISED PER ECO-16-009784	20JUN16	RS	GJ



POS.	DIM. A
3*5	33.70
3*4	27.70
3*3	21.70









- 1 MATERIAL:
LEVEL 1:PBT,STANDARD TEMPERATURE 105°C
KEY A:NATURAL; KEY B:PURPLE; KEY C:BLUE; KEY D:YELLOW

LEVEL 2:NYLON,HIGH TEMPERATURE 150°C
KEY A:LIGHT GREY; KEY B:RED; KEY C:BLACK; KEY D:NATURAL
- 2 MATERIAL MARK:
LEVEL 1:PBT,LEVEL 2:HDT
- 3 APPLICABLE CONTACT P/N
RECEPTACLE CONTACT:1971237/1971779/81/83/85/87-*, 2238066-*
- 4 MATING CONN. P/N
CAP HSG:*-1971874/5-*
DOUBLE ROW LOCK PLATE:*-1971778-*;SINGLE ROW LOCK PLATE:*-1971777-*

5 This product has not completed validation testing.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN TOMMY WU 09JUL2012		 TE Connectivity			
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±0.35 1 PLC ±0.25 2 PLC ±0.25 3 PLC ±0.25 4 PLC ±0.25 ANGLES ±0.5° FINISH	CHK HAPYE WU 09JUL2012					
		APVD YUZHONG MAO 09JUL2012	NAME				
		PRODUCT SPEC 108-106118	PLUG HOUSING, TRIPLE ROW POWER TRIPLE LOCK -				
		APPLICATION SPEC 114-106118					
	MATERIAL 	WEIGHT -	SIZE A1	CAGE CODE 00779	DRAWING NO 1971876	RESTRICTED TO -	
		Customer Drawing		SCALE 3:1	SHEET 1	OF 2	REV D

REVISIONS				
P	LYR	DESCRIPTION	DATE	APVD
	-	SEE SHEET 1	-	-






3*5	LEVEL 1	KEY A	1-1971876-7
		KEY B	2-1971876-7
		KEY C	3-1971876-7
		KEY D	4-1971876-7
3*4	LEVEL 2	KEY A	5-1971876-7
		KEY B	6-1971876-7
		KEY C	7-1971876-7
		KEY D	8-1971876-7
3*3	LEVEL 1	KEY A	1-1971876-4
		KEY B	2-1971876-4
		KEY C	3-1971876-4
		KEY D	4-1971876-4
	LEVEL 2	KEY A	5-1971876-4
		KEY B	6-1971876-4
		KEY C	7-1971876-4
		KEY D	8-1971876-4
POS.	MATERIAL	KEY	P/N

3*3 POSITIONS

3*4 POSITIONS

3*5 POSITIONS



KEYING FOR 3*5 POS.

KEYING FOR 3*3 POS.

KEYING FOR 3*4 POS.

THIS DRAWING IS A CONTROLLED DOCUMENT.

OWN TOMMY WU 09JUL2012

CHK HAPYE WU 09JUL2012

APVD YUZHONG MAO 09JUL2012

DIMENSIONS:

mm

0 PLC ±.35

1 PLC ±0.25

2 PLC ±.35

3 PLC ±.35

4 PLC ±.35

ANGLES FINISH

TOLERANCES UNLESS OTHERWISE SPECIFIED:

±.35

±0.25

±.35

±.35

±.35

±.35

MATERIAL

-

-

-

-

-

PRODUCT SPEC

108-106118

APPLICATION SPEC

114-106118

WEIGHT

-

Customer Drawing

NAME

PLUG HOUSING,TRIPLE ROW POWER TRIPLE LOCK

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

SCALE

-

SHEET

2

OF

2

REV

D

TE Connectivity

100779

1971876

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-1971876-3](#)