


THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

© COPYRIGHT - By -

LOC	DIST	REVISIONS						
		P	LTR	DESCRIPTION			DATE	
G	14			U1	REVISED PER ECO-11-004917		11MAR11	RK HMR



5.00 ± 0.08
[.197 ± 0.03]
FOR #10 STUD

1 STAMP AMP 22-16* APPROX AS SHOWN
22-16 TERMINALS ARE STAMPED 22-18 IN
ACCORDANCE WITH MILITARY SPEC MIL-T-7928
COMMERCIAL WIRE RANGE IS 22-16

2 WIRE INSULATION DIA: 2.67-3.56 [.105-.140]

3 TONGUE MATERIAL THK: 0.79 ± 0.05 [.031 ±.002]

4 MATERIAL: BODY - CU PER ASTM B152
SLEEVE - PVC, COLOR - RED

5 MATERIAL: BODY - CU PER ASTM B152
SLEEVE - PVC, COLOR - BLACK

6 REPLACED BY 8-34146-1

OBSOLETE	100	LOOSE PC,BOX SPL	8-34146-6
	50	LOOSE PC,BAG	8-34146-5
	5	LOOSE PC,BLS	8-34146-4
	100	LOOSE PC,BOX	8-34146-1
	5000	ON TAPE, REEL	2-34146-5
	1000	LOOSE PIECE	2-34146-4
	5000	ON TAPE, REEL	2-34146-1
	1000	LOOSE PIECE	34146
QTY		PACKAGE TYPE	PART NO.

**AMP INCORPORATED
CUSTOMER SERVICE SYSTEMS**

FOR ADDITIONAL
PRODUCT INFORMATION OR
COPIES OF DRAWINGS
AND TECHNICAL DOCUMENTS

PRODUCT INFORMATION CENTER
1-800-522-6752

FOR APPLICATION
TOOLING INFORMATION

TOOLING ASSISTANCE CENTER
1-800-722-1111

FOR ORDER ENTRY

1-800-526-5142

THIS DRAWING IS A CONTROLLED DOCUMENT FOR
AMP INCORPORATED. IT IS SUBJECT TO CHANGE
AND THE CONTROLLING ENGINEERING ORGANIZATION
SHOULD BE CONTACTED FOR THE LATEST REVISION.

MAX RECOMMENDED OPERATING
TEMPERATURE:

105°C [221°F]

VOLTAGE RATING:
600V MAX
(1000V FIXTURE OR SIGN)

CIRCULAR MIL AREA:

0.26-1.65mm² [509-3260]
SOLID OR STRANDED

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

TOLERANCES UNLESS
OTHERWISE SPECIFIED:
0 PLC $\pm -$
1 PLC $\pm -$
2 PLC $\pm 0.20[.008]$
3 PLC $\pm -$
4 PLC $\pm -$
ANGLES $\pm -$

MATERIAL

FINISH
SEE NOTES

TIN PER ASTM B545

DWN 08/06/92
DK SCHRUM

CHK 11/10/92
RE HERSEY

APVD 11/10/92
M BARNABA

PRODUCT SPEC

UL 486A

APPLICATION SPEC

—

WEIGHT —

—

CUSTOMER DRAWING



TE Connectivity

TERMINAL, RING TONGUE,
PLASTI-GRIP,
WIRE SIZE, 22-16 AWG

SIZE CAGE CODE DRAWING NO
A3 00779 C-34146
RESTRICTED TO
—

SCALE 4:1 SHEET 1 OF 1 REV U1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-34146-4](#) [2-34146-5](#)