

SPECIFICATION CONTROL DRAWING

55PC0746

TITLE
FOUR CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, 1000 VOLT

Date
12-9-96

Revision
B

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.

COMPONENT WIRES - 55PC0716



CONSTRUCTION DETAILS						
PART NUMBER	CONDUCTOR SIZE (AWG)	DIAMETER (in.)			WEIGHT (lbs/1000 ft.)	
		LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC0746-24-*	24	.122	.143	.164	11.68	12.15
55PC0746-22-*	22	.135	.158	.182	15.84	16.41
55PC0746-20-*	20	.153	.179	.205	22.35	23.05
55PC0746-18-*	18	.174	.205	.235	32.29	33.25
55PC0746-16-*	16	.191	.224	.256	40.04	41.15

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C
Maximum continuous conductor temperature
VOLTAGE RATING: 1000 volts (rms)
INSULATION FLAWS:
Impulse Dielectric test, 8.0 kV (peak)

PART NUMBER:
The "*" in the part numbers above shall be replaced by a color code designator with a slash separating the component wire colors.
Example: AWG 22, white, red, orange and yellow component wires: 55PC0746-22-9/2/3/4

COLOR AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681.

Raychem

Raychem Corporation
300 Constitution Drive, Menlo Park, California 94025
1-800-2 Raychem Fax: 1-415-361-6297

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[55PC0746-20-2/4/5/6CS2502](#)