



NOTES:

1. MATERIAL: THERMO PLASTIC POLYESTER; 30 % GF, UL-94-v0; COLOUR: GREY
2. DIFFERENTS TYPES HOLES:
TYPE 1: FOR RETENTION $\varnothing 0.68$ ON ROWS "a" AND "c" ON CAVITIES 1 TO 6, 15 TO 18 AND 27 TO 32
TYPE 2: $\varnothing 0.75$ ON OTHER HOLES ON ROWS "a" AND "c"
TYPE 3: $\varnothing 0.85$ ON HOLES ON ROW "b"
3. RETENTION OF CONNECTOR WITH ROWS "a" AND "c" ; FULLY LOADED 180N MIN
4. THE "LF" PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
5. LEADFREE OR RoHS DIRECTIVE LABELLING TO BE PROVIDED AS PER GS-14-920.
6. " LF " SUFFIX TO PRODUCT NUMBER FOR RoHS COMPATIBLE/ LEADFREE VERSION.
7. PARTS WITH AND WITHOUT "LF" SUFFIX ARE FORM-FIT AND FUNCTIONALLY IDENTICAL.
" LF " SUFFIX PROVIDED FOR PART NUMBER STANDARDISATION OF PART THAT MEETS RoHS REQUIREMENTS.

PRODUCT NUMBER
70017-001

mat'l. code SEE NOTES				surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection mm	product family BACKPANEL			
ltr	ecn no	dr	date	tolerances unless otherwise specified		mm	title B.P. SHROUD HIGH RETENTION			
D	F50459	OMA	1995-06-20	angles	linear					
E	F50955	OMA	1995-12-20			scale 2:1	dwg no 70017			
F	I06-0082	MINI	2006-06-01							
				dr	O.MATHEWVON	1995-05-03	FCI			
				engr	M.MEUNIER	1995-05-03				
				chr	RAKHEE GEORGE	2006-06-01				
				appd	RAKHEE GEORGE	2006-06-01				
sheet index	revision sheet	F	1				type Product Customer Drawing			

form: A3

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[70017-001LF](#)