

4805 (3/11)

- 1 ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- 2. TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- $\boxed{3}$  The noted dimensions apply at the intersection of the post and housing



4 HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK. POST: COPPER ALLOY.

5 FINISH: 0.000381 [.000015] GOLD ON CONTACT AREA, OVER 0.00127 [.000050] NICKEL, ENTIRE POST.

THIS DRAWING IS A CO	ontro
DIMENSIONS:	T OTI
mm [INCHES]	011
$\oplus$	0 PLC 1 PLC 2 PLC 3 PLC 4 PLC ANGLES
MATERIAL	FINISH

	2				1	
	DIST	P LTR		REVISIONS	DATE DWN APVD	
101	.19	99.06	ised per 39	ECO-14-000264 80	15JUL2014 NK MM 4-146501-0	,
[3.9 98.		[3.900] 96.52	38	78	3-146501-9	
[3.8 96.	84]	[3.800] 93.98				
[3.7	_	[3.700] 91.44	37 36	76	3-146501-8	
[3.6		[3.600] 88.90			3-146501-7	
	84]	[3.500] 86.36	35	72	3-146501-6	
	84]	[3.400] 83.82	34	70	3-146501-5	D
	84]	[3.300] 81.28	33	68	3-146501-4	
	84]	[3.200]	32	66	3-146501-3	
[3.1	84]	78.74	31	64	3-146501-2	
<u> </u>	84]	76.20	30	62	3-146501-1	
	84]	73.66 [2.900]	29	60	3-146501-0	
73. [2.8	25 84]	71.12 [2.800]	28	58	2-146501-9	
70. [2.7	71 84]	68.58 [2.700]	27	56	2-146501-8	
68. [2.6		66.04 [2.600]	26	54	2-146501-7	
65. [2.5	63 84]	63.50 [2.500]	25	52	2-146501-6	
63. [2.4	09	60.96 [2.400]	24	50	2-146501-5	
60. [2.3		58.42 [2.300]	23	48	2-146501-4	
58.	_	55.88 [2.200]	22	46	2-146501-3	С
55.	_	53.34 [2.100]	21	44	2-146501-2	
52.	_	50.80 [2.000]	20	42	2-146501-1	
50.	39	48.26	19	40	2-146501-0	
[1.9	85	[1.900] 45.72	18	38	1-146501-9	
45.		[1.800]	17	36	1-146501-8	
42.		[1.700]	16	34	1-146501-7	
40.		[1.600] _38.10	15	32	1-146501-6	
[1.5	69	[1.500]	14	30	1-146501-5	а. а
[1.4]	_	[1.400] 33.02	13		1-146501-4	
[1.3]	84] 61	[1.300] 30.48		28	1-146501-3	
[1.2]	84] 07	[1.200] 27.94	12	26	1-146501-2	
[1.1	84] 53	[1.100] 25.40				В
	84]	[1.000]	10	22	1-146501-1	а.
	34]	[.900]	9	20	1-146501-0	
	34]	[.800]	8	18	146501-9	
[.78	34]	[.700]	7	16	146501-8	
[.68		[.600]	6	14	146501-7	
14.0	34]	12.70	5	12	146501-6	
12. [.48	34]	10.16 [.400]	4	10	146501-5	
9.7 [.38		7.62 [.300]	3	8	146501-4	
7.2		5.08 [.200]	2	6	146501-3	
4.6 [.18		2.54 [.100]	1	4	146501-2	
2.	13 34]	_	_	2	146501-1	
G		F	_	NO. OF POSITIONS	PART NUMBER	А
A CONTROLLED DOCUME	СНК	11NC BRANDBERG 11NC		STE	TE Connectivity	1
O PLC ± -	D: APVD	<u>UBNICZKI</u> 11nc <u>UBNICZKI</u> 7 spec	V96 NAME		EMBLY, MOD II,	
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	] — 105] APPLICA	ATION SPEC	SIZE	STACKING, DOUBLE ROW, .025 SQ.POST, UNSHROUDED		
$\frac{10.012/1}{\text{ANGLES}}$	WEIGHT	_	A1	00779 <b>C-</b> 14650	)1 —	
	CUST	OMER DRAWING	3	SCALE	4:1 sheet 0 of 1 Rev R	

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>1-146501-0</u>