



- 1 CONNECTOR BODY AND COUPLING NUT MATERIAL: 6061-T6 ALUMINUM, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404E
LOCKING RING MATERIAL: BERYLLIUM COPPER, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404E
INSULATOR MATERIAL: LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138 OR POLYPHENYLENE SULFIDE (PPS) PER ASTM D4067
O-RING MATERIAL: FLUOROSILICONE
- 2 WIRE TERMINATION: 28 AWG SOLID, 30 AWG STRANDED WIRE OR SMALLER
- 3 LUBRICATE O-RING WITH PARKER SUPER-O-LUBE PRIOR TO INSTALLATION
- 4 THIS DRAWING ALSO IDENTIFIED AS NANO NICS 303-0034

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	M. STORRY	20 MAY 99	TE Connectivity			
DIMENSIONS: INCHES		CHK	E. PAULUS	11 JUN 99				
		APVD	S. KAIN	27 JAN 00	NAME			
		PRODUCT SPEC			PLUG ASSEMBLY, CIRCULAR, THREADED COUPLING, METAL, 44 POSITION			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC			SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
0 PLC ± -		—			A2	0PJN9	C=1589065	—
1 PLC ± -		—			SCALE 6:1			
2 PLC ± .010		WEIGHT —			SHEET 1 OF 1			
3 PLC ± .005		CUSTOMER DRAWING			REV H			
4 PLC ± -								
ANGLES ± 1°								
FINISH								
SEE NOTES								

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[TCM044PC2DMC20](#)