



Product: [3613](#) 

CAT6+ Horizontal, 4pr, UTP, LS-PVC Jkt, CMP

Product Description

CAT6+ (400MHz), 4-Pair, U/UTP-unshielded, Plenum-CMP, Premise Horizontal cable, 23 AWG solid bare copper conductors, dual FRPO/FEP insulation, patented X-spline Center Member, ripcord, Flammarrest® PVC jacket.

Technical Specifications

Product Overview

Suitable Applications:	Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments
------------------------	--

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
23	Solid	BC - Bare Copper	4

Conductor Count:	8
Total Number of Pairs:	4

Insulation

Material
PO/FEP - Polyolefin / Fluorinated Ethylene Propylene

Bonded-Pair:	N/A
--------------	-----

Color Chart

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Ripcord	Separator Material
PVC-LS - Polyvinyl Chloride (Low Smoke)	Flammarrest®	0.238 in	0.017 in	Yes	Patented X-Spline Center Member

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. DCR Unbalance
77 Ohm/km	3 %

Capacitance

Max. Capacitance Unbalance	Nom.Mutual Capacitance
330 pF/100m	15.5 pF/ft

Delay

Frequency [MHz]	Max. Delay	Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]	Typical Delay Skew
100 MHz	537.6 ns/100m	35 ns/100m	70 %	35 ns/100m

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted)
1 MHz	2.0 dB/100m	84.3 dB	82.3 dB	80.3 dB	80.3 dB	76.8 dB	73.8 dB	20.0 dB	100 ± 15
4 MHz	3.7 dB/100m	75.3 dB	73.3 dB	69.5 dB	69.5 dB	64.8 dB	61.8 dB	23.6 dB	100 ± 15
8 MHz	5.3 dB/100m	70.8 dB	68.8 dB	63.5 dB	63.5 dB	58.7 dB	55.7 dB	25.3 dB	100 ± 15
10 MHz	5.9 dB/100m	69.3 dB	67.3 dB	61.4 dB	61.4 dB	56.8 dB	53.8 dB	26.0 dB	100 ± 15
16 MHz	7.4 dB/100m	66.2 dB	64.2 dB	56.8 dB	56.8 dB	52.7 dB	49.7 dB	26.0 dB	100 ± 15
20 MHz	8.3 dB/100m	64.8 dB	62.8 dB	54.4 dB	54.4 dB	50.8 dB	47.8 dB	26.0 dB	100 ± 15
25 MHz	9.4 dB/100m	63.3 dB	61.3 dB	52.0 dB	52.0 dB	48.8 dB	45.8 dB	25.5 dB	100 ± 15
31.25 MHz	10.5 dB/100m	61.9 dB	59.9 dB	49.4 dB	49.4 dB	46.9 dB	43.9 dB	25.0 dB	100 ± 15
62.5 MHz	15.1 dB/100m	57.4 dB	55.4 dB	40.3 dB	40.3 dB	40.9 dB	37.9 dB	23.5 dB	100 ± 15
100 MHz	19.3 dB/100m	54.3 dB	52.3 dB	33.0 dB	33.0 dB	36.8 dB	33.8 dB	22.5 dB	100 ± 15
155 MHz	24.5 dB/100m	51.4 dB	49.4 dB	24.9 dB	24.9 dB	33.0 dB	30.0 dB	21.6 dB	100 ± 22
200 MHz	28.2 dB/100m	49.8 dB	47.8 dB	19.6 dB	19.6 dB	30.8 dB	27.8 dB	21.0 dB	100 ± 22
250 MHz	31.8 dB/100m	48.3 dB	46.3 dB	14.5 dB	14.5 dB	28.8 dB	25.8 dB	20.5 dB	100 ± 32
300 MHz	35.2 dB/100m	47.1 dB	45.1 dB	9.9 dB	9.9 dB	27.3 dB	24.3 dB	20.1 dB	100 ± 32
350 MHz	38.4 dB/100m	46.1 dB	44.1 dB	5.7 dB	5.7 dB	25.9 dB	22.9 dB	19.8 dB	100 ± 32
400 MHz	41.5 dB/100m	45.3 dB	43.3 dB	1.8 dB	1.8 dB	24.8 dB	21.8 dB	19.5 dB	100 ± 32
450 MHz	44.3 dB/100m	44.5 dB	42.5 dB			23.7 dB	20.7 dB	19.2 dB	100 ± 32
500 MHz	47.1 dB/100m	43.8 dB	41.8 dB			22.8 dB	19.8 dB	19.0 dB	100 ± 32
550 MHz	49.7 dB/100m	43.2 dB	41.2 dB			22.0 dB	19.0 dB	18.8 dB	100 ± 32
600 MHz	52.3 dB/100m	42.6 dB	40.6 dB			21.2 dB	18.2 dB	18.7 dB	100 ± 32
650 MHz	54.8 dB/100m	42.1 dB	40.1 dB			20.5 dB	17.5 dB	18.5 dB	100 ± 32

Segregation class according EN50174-2:	a
--	---

Voltage

UL Voltage Rating
300 V RMS

Temperature Range

Installation Temp Range:	0°C To +50°C
UL Temp Rating:	90°C
Storage Temp Range:	-20°C To +75°C
Operating Temp Range:	-20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	28 lbs/1000ft
Max Recommended Pulling Tension:	25 lbs
Min Bend Radius During Installation:	2.5 in
Min Bend Radius/Minor Axis:	1.0 in

Standards

NEC Articles:	800
NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
ISO/IEC Compliance:	11801 ed 2.2 (2011) Class E
CPR Euroclass:	Eca
Data Category:	Category 6
ANSI Compliance:	S-116-732-2013 Category 6, ANSI/NEMA WC-66 Category 6
Telecommunications Standards:	ANSI/TIA-568.2-D Category 6
IEEE Specification:	IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
Other Standards:	C(UL)US CMP 90C OR (UL) CMP-LP (0.6A) OR CL3P-LP (0.6A)
Third Party Performance Verification:	Category 6

Applicable Environmental and Other Programs

Environmental Space:	Plenum
----------------------	--------

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	Yes
EU CE Mark:	Yes
EU REACH SVHC Compliance (yyyy-mm-dd):	2017-07-10
EU RoHS Compliance Date (yyyy-mm-dd):	2009-04-03
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Aerial:	No
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	No
Suitability - Oil Resistance:	No
Suitability - Outdoor:	No
Suitability - Sunlight Resistance:	No

Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262 Plenum (UL 910)
CSA Flammability:	FT6
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

Part Number

Non-Plenum Number:	3612
--------------------	------

Variants

Item #	Color	Putup Type	Length	UPC
3613 0101000	Black	Reel	1,000 ft	612825145967
3613 010A1000	Black	Reel-in-Box	1,000 ft	612825145943
3613 010U1000	Black	UnReel	1,000 ft	612825145950
3613 0102500	Black	Reel	2,500 ft	612825145974
3613 D151000	Blue	Reel	1,000 ft	612825145714
3613 D15A1000	Blue	Reel-in-Box	1,000 ft	612825335078
3613 D15U1000	Blue	UnReel	1,000 ft	612825335085
3613 D152500	Blue	Reel	2,500 ft	612825145721
3613 0081000	Gray	Reel	1,000 ft	612825145899
3613 008A1000	Gray	Reel-in-Box	1,000 ft	612825145875
3613 008U1000	Gray	UnReel	1,000 ft	612825145882
3613 0051000	Green	Reel	1,000 ft	612825145837
3613 005A1000	Green	Reel-in-Box	1,000 ft	612825145813
3613 005U1000	Green	UnReel	1,000 ft	612825145820
3613 0052500	Green	Reel	2,500 ft	612825145844
3613 0031000	Orange	Reel	1,000 ft	612825145769
3613 003A1000	Orange	Reel-in-Box	1,000 ft	612825145745
3613 003U1000	Orange	UnReel	1,000 ft	612825145752
3613 012A1000	Pink	Reel-in-Box	1,000 ft	612825145981

3613 007A1000	Purple	Reel-in-Box	1,000 ft	612825145851
3613 007U1000	Purple	UnReel	1,000 ft	612825145868
3613 002A1000	Red	Reel-in-Box	1,000 ft	612825145738
3613 0091000	White	Reel	1,000 ft	612825145929
3613 009A1000	White	Reel-in-Box	1,000 ft	612825145905
3613 009U1000	White	UnReel	1,000 ft	612825145912
3613 0092500	White	Reel	2,500 ft	612825145936
3613 0041000	Yellow	Reel	1,000 ft	612825145790
3613 004A1000	Yellow	Reel-in-Box	1,000 ft	612825145776
3613 004U1000	Yellow	UnReel	1,000 ft	612825145783
3613 0042500	Yellow	Reel	2,500 ft	612825145806

Patent:	https://www.belden.com/resources/patents
---------	---

Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Values above 400 MHz are for Engineering Information Only. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0.
--------	--

History

Update and Revision:	Revision Number: 0.393 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

[3613 008U1000](#) [3613 009U1000](#) [3613 D15U1000](#) [3613 D15A1000](#) [3613 D151000](#) [3613 D152500](#) [3613 002A1000](#)
[3613 003A1000](#) [3613 0031000](#) [3613 004A1000](#) [3613 0041000](#) [3613 0042500](#) [3613 005A1000](#) [3613 0051000](#)
[3613 0052500](#) [3613 007A1000](#) [3613 008A1000](#) [3613 0081000](#) [3613 009A1000](#) [3613 0091000](#) [3613 0092500](#) [3613](#)
[010A1000](#) [3613 0101000](#) [3613 0102500](#) [3613 012A1000](#)