


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** [0765003107](#)  
**Status:** **Active**  
**Overview:** [Impact Backplane Connector and Cable Assembly System](#)  
**Description:** Impact 100 Ohm 4 Pair RAM Right-Angle Header, Left Guided, Open Endwall, 10 Columns, 120 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free



|                                                                  |                                                                   |
|------------------------------------------------------------------|-------------------------------------------------------------------|
| <b>Documents:</b>                                                |                                                                   |
| <a href="#">3D Model</a>                                         | <a href="#">Application Specification AS-76060-994-001 (PDF)</a>  |
| <a href="#">Drawing (PDF)</a>                                    | <a href="#">Application Specification AS-76060-9999-001 (PDF)</a> |
| <a href="#">Product Specification PS-76060-999-001 (PDF)</a>     | <a href="#">Packaging Specification PK-70873-041-001 (PDF)</a>    |
| <a href="#">Application Specification AS-76060-990-001 (PDF)</a> | <a href="#">RoHS Certificate of Compliance (PDF)</a>              |

**Agency Certification**

UL E29179

**General**

|                               |                                                                      |
|-------------------------------|----------------------------------------------------------------------|
| Product Family                | Backplane Connectors                                                 |
| Series                        | <a href="#">76500</a>                                                |
| Application                   | Coplanar                                                             |
| Application Tooling Documents | TM-622018799                                                         |
| Component Type                | PCB Header                                                           |
| Overview                      | <a href="#">Impact Backplane Connector and Cable Assembly System</a> |
| Product Name                  | Impact                                                               |
| UPC                           | 883906873691                                                         |

**Physical**

|                                |                                |
|--------------------------------|--------------------------------|
| Circuits (Loaded)              | 120                            |
| Circuits (maximum)             | 120                            |
| Color - Resin                  | Black                          |
| Durability (mating cycles max) | 200                            |
| First Mate / Last Break        | No                             |
| Flammability                   | 94V-0                          |
| Guide to Mating Part           | Yes                            |
| Keying to Mating Part          | None                           |
| Material - Metal               | High Performance Alloy (HPA)   |
| Material - Plating Mating      | Gold                           |
| Material - Plating Termination | Tin                            |
| Material - Resin               | High Temperature Thermoplastic |
| Net Weight                     | 17.277/g                       |
| Number of Columns              | 10                             |
| Number of Pairs                | 4                              |
| Number of Rows                 | 12                             |
| Orientation                    | Right Angle                    |
| PC Tail Length                 | 1.20mm                         |
| PCB Locator                    | No                             |
| PCB Retention                  | Yes                            |
| PCB Thickness - Recommended    | 1.00mm                         |
| Packaging Type                 | Tray                           |
| Pitch - Mating Interface       | 1.90mm                         |
| Pitch - Termination Interface  | 1.90mm                         |
| Plating min - Mating           | 0.762µm                        |
| Polarized to PCB               | Yes                            |
| Stackable                      | No                             |
| Temperature Range - Operating  | -55° to +85°C                  |
| Termination Interface: Style   | Through Hole - Compliant Pin   |

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
ED/71/2019 (16 July  
2019)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[76500](#) Series

**Mates With**

[76160](#) Impact 100 Ohm Daughtercard

**Application Tooling | FAQ**

*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*

**Global**

| Description         | Product #                 |
|---------------------|---------------------------|
| Daughter Card       | <a href="#">622018641</a> |
| Module Installation |                           |
| Press-In Tool       |                           |
| Impact Right-Angle  | <a href="#">622024350</a> |
| Module Removal      |                           |
| Tool (RAM)          |                           |

**Electrical**

|                               |                 |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 0.75A           |
| Data Rate                     | 25.0 Gbps       |
| Impedance                     | 100Ω            |
| Shield Type                   | N/A             |
| Shielded                      | No              |
| Voltage - Maximum             | 30V AC (RMS)/DC |

**Solder Process Data**

|                             |     |
|-----------------------------|-----|
| Lead-freeProcess Capability | N/A |
|-----------------------------|-----|

**Material Info**

**Reference - Drawing Numbers**

|                           |                                                          |
|---------------------------|----------------------------------------------------------|
| Application Specification | AS-76060-990-001, AS-76060-994-001,<br>AS-76060-9999-001 |
| Electrical Model Document | EE-76500-002                                             |
| Packaging Specification   | PK-70873-041-001                                         |
| Product Specification     | PS-76060-999-001                                         |
| S-Parameter Model         | SP-76500-002                                             |
| Sales Drawing             | SD-76500-002                                             |
| Symbol/Footprint Data     | SYM-76500-3107                                           |

This document was generated on 10/22/2019

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[76500-3107](#)