

XPSMP11123

module XPS-MP - 2 independent functions - 24 V DC

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Commercial Status	Commercialised
Range of product	Preventa Safety automation
Product or component type	Safety controller with pre-defined function
Safety module name	XPSMP
Safety module application	2 independent functions
Safety use category	Category 4 maximum conforming to EN/IEC 60954-1
Type of start	Monitored (configuration 9) Monitored (configuration 8) Monitored (configuration 6) Monitored (configuration 4) Monitored (configuration 2) Monitored (configuration 15) Monitored (configuration 13) Monitored (configuration 12) Automatic or unmonitored (configuration 7) Automatic or unmonitored (configuration 5) Automatic or unmonitored (configuration 3) Automatic or unmonitored (configuration 14) Automatic or unmonitored (configuration 11) Automatic or unmonitored (configuration 10) Automatic or unmonitored (configuration 1)
Checks	Configuration (configuration 9) Configuration (configuration 6) Configuration (configuration 5) Configuration (configuration 4) Configuration (configuration 3) Configuration (configuration 13) Configuration (configuration 10)
Standards	DIN V VDE 801 + A1 EN/IEC 60204-1 EN/IEC 60947-1 + A11 EN/IEC 60947-5-1
Product certifications	BIA CSA UL
[Us] rated supply voltage	24 V DC (- 20...20 %)
Connections - terminals	Captive screw clamp terminals: 0.5...1.5 mm ² , 2 wires flexible with cable end, with double bezel Captive screw clamp terminals: 0.25...2.5 mm ² , 1 wire flexible with cable end, without bezel Captive screw clamp terminals: 0.25...1.5 mm ² , 1 wire flexible with cable end, with bezel Captive screw clamp terminals: 0.25...1 mm ² , 2 wires flexible with cable end, without bezel Captive screw clamp terminals: 0.14...2.5 mm ² , 1 wire solid without cable end Captive screw clamp terminals: 0.14...2.5 mm ² , 1 wire flexible without cable end Captive screw clamp terminals: 0.14...0.75 mm ² , 2 wires solid without cable end Captive screw clamp terminals: 0.14...0.75 mm ² , 2 wires flexible without cable end
Safety level	Can reach SIL 3 conforming to EN/IEC 62061 Can reach PL e/category 4 conforming to EN/ISO 13849-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Complementary

Function of module	<p>Configuration 9: guard monitoring for injection presses and blowing machines, category 4</p> <p>Configuration 8: emergency stop monitoring 2-channel wiring, or guard monitoring, category 4</p> <p>Configuration 7: emergency stop monitoring 2-channel wiring, or guard monitoring, category 4</p> <p>Configuration 6: emergency stop monitoring 2-channel wiring, or guard monitoring, category 4</p> <p>Configuration 5: emergency stop monitoring 2-channel wiring, or guard monitoring, category 4</p> <p>Configuration 4: emergency stop monitoring 2-channel wiring, or guard monitoring, category 4</p> <p>Configuration 3: emergency stop monitoring 2-channel wiring, or guard monitoring, category 4</p> <p>Configuration 2: emergency stop monitoring 1-channel wiring, category 2</p> <p>Configuration 15: coded magnetic switch monitoring, category 4</p> <p>Configuration 14: coded magnetic switch monitoring, category 4</p> <p>Configuration 13: relay output safety light curtain monitoring, category 4</p> <p>Configuration 12: sensing mat and edges monitoring, category 3</p> <p>Configuration 11: sensing mat and edges monitoring, category 3</p> <p>Configuration 10: enabling grip switch monitoring (3-position switch), category 4</p> <p>Configuration 1: emergency stop monitoring 1-channel wiring, category 2</p> <p>Configuration 0: functions disabled (factory setting)</p>
Synchronisation time between inputs	<p>Unlimited (configuration 8)</p> <p>Unlimited (configuration 7)</p> <p>Unlimited (configuration 4)</p> <p>Unlimited (configuration 3)</p> <p>1.5 s (configuration 9)</p> <p>1.5 s (configuration 6)</p> <p>1.5 s (configuration 5)</p> <p>1.5 s (configuration 15)</p> <p>1.5 s (configuration 14)</p> <p>0.5 s (configuration 13)</p>
Power consumption	<= 5 W
Input protection type	Internal, electronic
[Uc] control circuit voltage	24 V
Line resistance	100 Ohm, cable length: <= 6561.68 ft (2000 m)
Number of safety circuits	3 NO relays per function (6 NO total), volt-free
Number of additional circuits	3 solid state outputs
Breaking capacity	<p>C300: inrush 1800 VA AC-15 for relay output</p> <p>C300: holding 180 VA AC-15 for relay output</p>
Breaking capacity	<p>1.5 A/24 V - L/R = 50 ms, DC-13 for relay output</p> <p>20 mA/24 V for static output circuit</p>
Output thermal current	<p>6 A for 1 output and 2 A for the other 2 outputs for relay</p> <p>3.3 A for all 3 outputs relay simultaneously</p> <p>2 A for 1 output and 4 A for the other 2 outputs for relay</p>
[Ith] conventional free air thermal current	<= 20 A
Associated fuse rating	<p>6 A fast blow for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200</p> <p>4 A gG for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200</p>
Minimum output current	10 mA for relay output
Minimum output voltage	17 V for relay output
Response time on input open	< 30 ms
[Ui] rated insulation voltage	300 V, degree of pollution 2 conforming to EN/IEC 60947-5-1, DIN VDE 0110 parts 1 & 2
[Uimp] rated impulse withstand voltage	4 kV overvoltage category III conforming to EN/IEC 60947-5-1, DIN VDE 0110 parts 1 & 2
Local signalling	12 LEDs
Mounting support	35 mm symmetrical DIN rail
Depth	4.49 in (114 mm)
Height	3.9 in (99 mm)
Width	1.77 in (45 mm)
Product weight	0.71 lb(US) (0.32 kg)

Environment

IP degree of protection	IP40 (enclosure) IP20 (terminals)
Ambient air temperature for operation	14...131 °F (-10...55 °C)
Ambient air temperature for storage	-13...185 °F (-25...85 °C)

Ordering and shipping details

Category	22477 - SAFETY MODULES (PREVENTA)
Discount Schedule	I11
GTIN	00785901603429
Nbr. of units in pkg.	1
Package weight(Lbs)	0.71
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	ID

Contractual warranty

Period	18 months
--------	-----------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XPSMP11123](#)