



BTE-040-02-L-D-A



BTE-060-02-F-D-A



BTE, BSE SERIES

(0.80 mm) .0315"

BASIC BLADE & BEAM HEADER & SOCKET

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?BTE or www.samtec.com?BSE

Insulator Material: Liquid Crystal Polymer
Contact Material: Phosphor Bronze
Plating: Au or Sn over 50 μ" (1.27 μm) Ni
Current Rating: 2 A per pin (2 pins powered)
Operating Temp Range: -55 °C to +125 °C
Voltage Rating: 225 VAC with 5 mm Stack Height
Max Cycles: 100
RoHS Compliant: Yes

PROCESSING

Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0.10 mm) .004" max (020-080) (0.15 mm) .006" max (100-120)*
 *(.004" stencil solution may be available; contact IPG@samtec.com)
Board Stacking: For applications requiring more than two connectors per board or 80 positions or higher, contact ipg@samtec.com

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



ALSO AVAILABLE (MOQ Required)

- 30 μ" (0.76 μm) Gold
- Edge Mount Capability
- Friction Lock option
- 11 mm, 14 mm, 16.10 mm, 19.10 mm, 22 mm, 25 mm and 30 mm Stack Height (Caution: Some automatic placement/inspection machines may have component height restrictions. Please consult machinery specifications.)

Note: Some lengths, styles and options are non-standard, non-returnable.

| BTE | NO. OF POSITIONS PER ROW | LEAD STYLE | PLATING OPTION | D | A | OTHER OPTION | | | | | | |
|---|---------------------------------|---|---|----------|-------------|---|--|-------------|--|--|--|--|
| Mates with: BSE | | Specify LEAD STYLE from chart | -F = Gold Flash on contact, Matte Tin on tail | | | -K = (7.00 mm) .275" DIA Polyimide Film Pick & Place Pad | | | | | | |
| -020, -040, -060, -080, -100, -120 | | | -L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail | | | | -TR = Tape & Reel (80 positions maximum) | | | | | |
| | | <table border="1"> <tr> <th>LEAD STYLE</th> <th>A</th> </tr> <tr> <td>-01</td> <td>(4.27) .168</td> </tr> <tr> <td>-02</td> <td>(7.21) .284</td> </tr> </table> | LEAD STYLE | A | -01 | (4.27) .168 | -02 | (7.21) .284 | -C* = Electro-Polished Selective 50 μ" (1.27 μm) min Au over 150 μ" (3.81 μm) Ni on Signal Pins in contact area, Matte Tin over 50 μ" (1.27 μm) min Ni on all solder tails | | | |
| LEAD STYLE | A | | | | | | | | | | | |
| -01 | (4.27) .168 | | | | | | | | | | | |
| -02 | (7.21) .284 | | | | | | | | | | | |
| MATED HEIGHT | | | *Note: -C Plating passes 10 year MFG testing | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>LEAD STYLE</th> <th>MATED HEIGHT*</th> </tr> </thead> <tbody> <tr> <td>-01</td> <td>(5.00) .197</td> </tr> <tr> <td>-02</td> <td>(8.00) .315</td> </tr> </tbody> </table> | | LEAD STYLE | MATED HEIGHT* | -01 | (5.00) .197 | -02 | (8.00) .315 | | | | | |
| LEAD STYLE | MATED HEIGHT* | | | | | | | | | | | |
| -01 | (5.00) .197 | | | | | | | | | | | |
| -02 | (8.00) .315 | | | | | | | | | | | |
| | | | | | | POWER/SIGNAL APPLICATION | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | Compatible with UMPT/UMPS for flexible two-piece power/signal solutions | | | | | | |

| | | | | | | |
|---|---------------------------------|-----------|--|----------|----------|--|
| BSE | NO. OF POSITIONS PER ROW | 01 | PLATING OPTION | D | A | OTHER OPTION |
| Mates with: BTE | | | -F = Gold Flash on contact, Matte Tin on tail | | | -TR = Tape & Reel (80 positions maximum) |
| -020, -040, -060, -080, -100, -120 | | | -L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail | | | |
| | | | -C* = Electro-Polished Selective 50 μ" (1.27 μm) min Au over 150 μ" (3.81 μm) Ni on Signal Pins in contact area, Matte Tin over 50 μ" (1.27 μm) min Ni on all solder tails | | | |
| *Note: -C Plating passes 10 year MFG testing | | | | | | |
| | | | | | | |

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

[BSE-020-01-F-D-A](#) [BSE-040-01-L-D-A](#) [BSE-060-01-F-D-A](#) [BSE-060-01-L-D-A-TR](#) [BSE-060-01-L-D-A](#) [BSE-020-01-F-D-A-TR](#) [BSE-080-01-L-D-A](#) [BSE-060-01-F-D-A-TR](#) [BSE-020-01-L-D-A-TR](#) [BSE-040-01-F-D-A](#) [BSE-020-01-L-D-A](#) [BSE-040-01-L-D-A-TR](#) [BSE-040-01-F-D-A-TR](#) [BSE-080-01-F-D-A-TR](#) [BSE-040-01-L-D](#) [BSE-040-01-H-D-A](#) [BSE-040-01-L-D-EM2](#) [BSE-080-01-L-D-A-TR](#) [BSE-100-01-H-D-A](#) [BSE-020-01-H-D-A](#) [BSE-120-01-L-D-EM2](#) [BSE-080-01-H-D-A](#) [BSE-060-01-H-D-A](#) [BSE-120-01-H-D-A](#) [BSE-090-01-L-D-A](#) [BSE-080-01-H-D](#) [BSE-040-01-C-D-A](#) [BSE-060-01-F-D-EM2-GP](#) [BSE-020-01-C-D-A](#) [BSE-060-01-C-D-A](#) [BSE-040-01-C-D-A-TR](#) [BSE-060-01-C-D-A-TR](#) [BSE-060-01-L-D-A-FL](#) [BSE-020-01-L-D-TR](#) [BSE-080-01-F-D](#) [BSE-120-01-L-D-A](#) [BSE-060-01-L-D](#) [BSE-100-01-F-D-A](#) [BSE-020-01-F-D](#) [BSE-100-01-L-D-A](#) [BSE-020-01-L-D](#) [BSE-040-01-F-D](#) [BSE-060-01-F-D](#) [BSE-060-01-F-D-TR](#) [BSE-120-01-F-D-A](#) [BSE-040-01-L-D-A-FL](#) [BSE-060-01-F-D-LC](#) [BSE-040-01-F-D-EM2](#) [BSE-060-01-L-D-LC](#) [BSE-060-01-F-D-EM2](#) [BSE-020-01-F-D-EM2](#) [BSE-040-01-F-D-LC](#) [BSE-120-01-F-D](#) [BSE-120-01-L-D](#) [BSE-080-01-H-D-EM2](#) [BSE-020-01-L-D-FL](#) [BSE-080-01-F-D-LC](#) [BSE-020-01-F-D-A-FL-TR](#) [BSE-120-01-H-D-LC](#) [BSE-060-01-L-D-FL](#) [BSE-080-01-F-D-EM2](#) [BSE-040-01-L-D-TR](#) [BSE-020-01-F-D-A-FL](#) [BSE-040-01-F-D-A-FL](#) [BSE-080-01-H-D-A-TR](#) [BSE-020-01-H-D-A-TR](#) [BSE-020-01-L-D-A-FL](#) [BSE-020-01-L-D-EM2-GP](#) [BSE-080-01-L-D-A-FL](#) [BSE-080-01-L-D-EM2](#) [BSE-100-01-L-D-FL](#) [BSE-020-01-L-D-EM2](#) [BSE-060-01-H-D-A-TR](#) [BSE-080-01-L-D](#) [BSE-020-01-L-D-A-FL-TR](#) [BSE-080-01-F-D-A](#) [BSE-080-01-C-D-A](#)