



CUSTOMER DRAWING
SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE



- 1. MATERIAL:
HEAT SINK: ALUMINUM
CLIP: BLACK PEI (UL94-VO)
- 2. BEFORE THE HEATSINK APPLICATION, THE USER SHOULD IDENTIFY THE SPECIFICATION OF MAXIMUM LOAD ON THE BGA PACKAGE.
SCREW DRIVER SLOT (.070 WIDE X .100 DEEP) PROVIDED IN THE CENTER PORTION OF THE HEAT SINK. FOR ACCURATE TORQUE SETTING, SCREW DRIVER BIT MUST BE ALIGNED TO THE CENTER LINE OF THE HEAT SINK.
HEATSINK TORQUE SPECIFICATIONS CONVERTED TO FORCE. BARE DIE PACKAGE:
2.0 POUND-FORCE INCH TORQUE = 8.1 POUND-FORCE (0.23 NEWTON METER TORQUE = 36.03 NEWTON)
2.5 POUND-FORCE INCH TORQUE = 10.1 POUND-FORCE (0.28 NEWTON METER TORQUE = 44.93 NEWTON)
FULL SIZE LID PACKAGE:
2.0 POUND-FORCE INCH TORQUE = 6.9 POUND-FORCE (0.23 NEWTON METER TORQUE = 30.69 NEWTON)
2.5 POUND-FORCE INCH TORQUE = 8.7 POUND-FORCE (0.28 NEWTON METER TORQUE = 38.70 NEWTON)
- 3. REMOVE CLIP WITH REMOVAL TOOL P/N: 1542616-1
- 4. RoHS COMPLIANT AND CERTIFIED.

Table with 3 columns: ITEM NO., DESCRIPTION, QTY. Rows include Interface, Heatsink, and Mounting Clip.

Table with 7 columns: Thermal Performance (200 LFM, 400 LFM, 600 LFM, Rca), Assembly HS Part No., Description, Ø"B", and DIM "A". Rows list various assembly configurations.

Revision history table with columns: REV., DESCRIPTION, DATE, APP'D. Rows show revisions A through D.

Footer section containing Tyco Electronics logo, contact information, release status, and title block details.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1963557-2](#)