

REV. 0


DCO 143325

COIL: @ 25°C
 RESISTANCE 390 OHMS ±10%
 NOMINAL VOLTAGE 12.0 VDC
 MUST OPERATE 8.0 VDC
 MUST RELEASE 5.2 VDC MAX, 1.1 VDC MIN.

ENVIRONMENT:
 VIBRATION 10 CPS TO 3000 CPS @ 30 g's
 SHOCK 75 g's 6 MS. DURATION
 TEMPERATURE -65 °C TO +125 °C

NOTES: OPERATE TIME 2.0 MS MAX
RELEASE TIME 4.0 MS MAX
CONTACT STABILIZATION 2.5 MS MAX.

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: LOW LEVEL TO 1 AMP
28 VDC RESISTIVE 100,000 OPERATIONS

DR. ASB 11/26/01

Handwritten signature and date: 11/26/01

CII Technologies
 advanced control electronic solutions

CUST. OPL
 CUST. NO. M39016/19-028M REV. _____

"JMGADD" RELAY

JMGAPDD-12M

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMGAPDD-12M](#)