


THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION	- , - .
© COPYRIGHT - By -	ALL RIGHTS RESERVED.	

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A1	ECR-14-015049	13OCT2014	GSK	BvH
	A2	ECR-16-003945	16MAR2016	GSK	BvH

NOTES:

Tolerances cable lengths:


0m to 0.5m	+30mm
0.5m to 1.0m	+50mm
1.0m to 3.0m	+100mm
< 3.0m	+1.5%



TECHNICAL DATA	
Operating voltage	24 V DC ±25 %
Operating current per contact	max. 4 A
Locking of ports	Screw thread M12 x 1 mm (recommended torque 0.6 Nm) self-securing
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)

PUR/PVC CABLE	
No./diameter of wires	5 x 0.34 mm ²
Wire isolation	PVC (br, wh, bl, bk, gnye)
C-track properties	2 million
Jacket	PUR/PVC
Outer diameter	approx. 5.9 mm
Bend radius (moving)	15 x outer diameter
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-5...+80 °C

CABLE	
No./diameter of wires	5 x 0.34 mm ²
Wire isolation	PP (br, wh, bl, bk, gnye)
C-track properties	10 million
Jacket	PUR (UL/CSA), welding spark res.
Outer diameter	approx. 5.0 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	-40...+90 °C
Temperature range (mobile)	-25...+90 °C



5 pos	2.0mtr	SPARK RESISTANT	Black	3-2273127-5	5x22AWG SPARK RES 2.0m	20
	1.5mtr			3-2273127-4	5x22AWG SPARK RES 1.5m	19
	1.0mtr			3-2273127-3	5x22AWG SPARK RES 1.0m	18
	0.6mtr			3-2273127-2	5x22AWG SPARK RES 0.6m	17
	0.3mtr			3-2273127-1	5x22AWG SPARK RES 0.3m	16
	5 pos			2.0mtr	PUR/PVC	Black
1.5mtr		2-2273127-4	5x22AWG PUR/PVC 1.5m	14		
1.0mtr		2-2273127-3	5x22AWG PUR/PVC 1.0m	13		
0.6mtr		2-2273127-2	5x22AWG PUR/PVC 0.6m	12		
0.3mtr		2-2273127-1	5x22AWG PUR/PVC 0.3m	11		
		LENGTH"L"	MATERIAL	JACKET COLOR		

TECHNICAL DATA	
Operating voltage	24 V DC $\pm 25\%$
Operating current per contact	max. 4 A
Locking of ports	Screw thread M12 x 1 mm (recommended torque 0.6 Nm) self-securing
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)

PUR CABLE	
No./diameter of wires	5 x 0.34 mm ²
Wire isolation	PP (br, wh, bl, bk, gnye)
C-track properties	5 million
Jacket	PUR (UL/CSA)
Outer diameter	approx. 5.0 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	-40...+80 °C
Temperature range (mobile)	-25...+80 °C

PVC CABLE	
No./diameter of wires	5 x 0.34 mm ²
Wire isolation	PVC (br, wh, bl, bk, gnye)
C-track properties	
Jacket	PVC (UL/CSA)
Outer diameter	approx. 5.2 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-5...+80 °C

5	pos	2.0mtr	PVC	Black	1—2273127—5	5x22AWG PVC 2.0m	10
		1.5mtr			1—2273127—4	5x22AWG PVC 1.5m	9
		1.0mtr			1—2273127—3	5x22AWG PVC 1.0m	8
		0.6mtr			1—2273127—2	5x22AWG PVC 0.6m	7
		0.3mtr			1—2273127—1	5x22AWG PVC 0.3m	6
5	pos	2.0mtr	PUR	Black	2273127—5	5x22AWG PUR 2.0m	5
		1.5mtr			2273127—4	5x22AWG PUR 1.5m	4
		1.0mtr			2273127—3	5x22AWG PUR 1.0m	3
		0.6mtr			2273127—2	5x22AWG PUR 0.6m	2
		0.3mtr			2273127—1	5x22AWG PUR 0.3m	1
	LENGTH" L "	MATERIAL	JACKET COLOR	TE PN	DESCRIPTION	ITEM	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN YATHISH.C 02DEC2013		 TE Connectivity					
		CHK B.VELDHOVEN 02DEC2013							
DIMENSIONS: mm		TOLERANCES, UNLESS OTHERWISE SPECIFIED:		NAME M12 ANGLD SCKT TO M12 STRGHT PLG 3 LED					
		APVD A.VAN ZANDVOORT 02DEC2013 PRODUCT SPEC 108-19483 APPLICATION SPEC 114-32127				SIZE		CAGE CODE	
MATERIAL -		FINISH -		WEIGHT		DRAWING NO		RESTRICTED TO	
				A2 00779		C=2273127		-	
CUSTOMER DRAWING				SCALE		SHEET		REV	
				NTS		1 of 1		A2	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-2273127-1](#)