









- | | |
|---|--|
| 1 | THE TIPS OF THE POSTS WILL NOT BE PLATED |
| 2 | THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND THE HOUSING |
| 3 | POINT OF MEASUREMENT FOR PLATING THICKNESS |
| 4 | OBsolete PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI |



TO SUPPORT MATING
CONNECTOR ON BOARD



FOR MOUNTING HEADER
FLUSH TO BOARD EDGE



KEYWAY LOCATIONS (REF-SEE TABLE)
(MATING LENGTH OF POST ON NEAR SIDE)
SCALE: 2:1

 OBSOLETE	A,C,E,H,K,M,Q,S,U,W,Y	1 1	3.855	3.744	24	25	2-87654-5-
	A,C,E,G,J,L,N,Q,S,U,W,Y	12	3.699	3.588	23	24	2-87654-4-
	A,D,G,K,N,R,U,X	8	3.543	3.432	22	23	2-87654-3-
	A,C,E,G,J,L,N,Q,S,U,W	1 1	3.387	3.276	21	22	2-87654-2-
	A,D,G,K,N,R,U	7	3.231	3.120	20	21	2-87654-1-
	A,C,E,G,J,L,N,Q,S,U	10	3.075	2.964	19	20	2-87654-0-
	B,D,F,J,L,N,Q,S	8	2.919	2.808	18	19	1-87654-9-
 OBSOLETE	A,D,F,J,M,P,S	7	2.763	2.652	17	18	1-87654-8-
	A,D,G,K,N,R	6	2.607	2.496	16	17	1-87654-7-
	A,C,E,G,J,L,N,Q	8	2.451	2.340	15	16	1-87654-6-
	A,D,G,K,N	5	2.295	2.184	14	15	1-87654-5-
	A,C,E,G,J,L,N	7	2.139	2.028	13	14	1-87654-4-
	A,D,J,M	4	1.983	1.872	12	13	1-87654-3-
	A,C,E,G,J,L	6	1.827	1.716	11	12	1-87654-2-
	A,D,G,K	4	1.671	1.560	10	11	1-87654-1-
	A,C,E,G,J	5	1.515	1.404	9	10	1-87654-0-
	A,D,G	3	1.359	1.248	8	9	1-87654-9-
 OBSOLETE	A,C,E,G	4	1.203	1.092	7	8	1-87654-8-
	A,C,E	3	1.047	.936	6	7	1-87654-7-
	A,C,E	3	.891	.780	5	6	1-87654-6-
	A,D	2	.735	.624	4	5	1-87654-5-
	A,C	2	.579	.468	3	4	1-87654-4-
	A	1	.423	.312	2	3	1-87654-3-
	A	1	.267	.156	1	2	1-87654-2-
KEYWAY LOCATIONS		NO OF KEYWAY	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN 164887 L.A. MAYER		Tycos Electronics Corporation Harrisburg, Pa 17105-3608	
DIMENSIONS:		CHK F.B. HUBBEN 19MAR87			
INCHES		APVD F.B. HUBBEN 19MAR87			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-87654-8](#)