General-Purpose Transistors




Sanyo general-purpose transistors are designed to meet every high-performance requirement.

They have wide application. They are easy to use because of large current capacity and wide ASO.

& Small-signal Transistors.

(*:Tc=25°C). PNP, (-)sign is omitted.

Type No.	Package	Absolute Maximum Ratings/Ta=25℃					Electrical Characteristics/Ta=25℃									
		V CBO	V CEO (V)	I _C (A)	P _C (₩)	V CE (V)	I C (mA)	h FE	V CE (V)	I C (mA)	f T (MHz)	I C (mA)	I B (mA)	V CE(sat) max (V)		
2SA1622(M) 2SC4211(L)	МСР	55	50	0. 15	0. 15	6		135 ~ 600	6	10	180 200	50	5	0.4		
2SA1781(GS) 2SC4639(VT)	СР	55	50	0. 15	0.2		1	135 ~ 600		10	180 200	50	5	0.4		
2SA1782 2SC4640	SPA	55	50	0. 15	0.3			140 ~ 560		10	180 200	50	5	0.4		
2SA1783 2SC4641	NP	55	50	0. 15	0.5			140 ~ 560		10	180 200	50	5	0.4		
2SB1142 2SD1682	TO-126 ML	60	50	2. 5	1.5 *10	2	100	100 ~ 400 100 ~ 560		50	140	1000	50	0.5 0.3		




Type No.	Package	Absolute Maximum Ratings/Ta=25°C				Electrical Characteristics/Ta=25°C								
		V _{CBO}	V _{CEO}	I _C	P _C Tc=25°C (W)	V _{CE}	I _C	h _{FE}	(V)	I _C	f typ (MHz)	I _C	I _B	V CE(sat) max (V)
2SB1133 2SD1666	TO-220ML	60	60 60	3	25	5	0.5	70 ~ 280	5	0.5	40 8	- 2	0.2	1
2SB1274 2SD1913		80			20	5	0.5	70 ~ 280			100			

h F E Rank Classification.

70 Q 140 100 R 200 140 S 280


Case Outlines(unit:mm) 1:Base, 2:Collecter, 3:Emitter SANYO:TO-220ML




These specifications are subject to change without notice.



SANYO Discrete Device Package Outlines(unit:mm)



SANYO Discrete Device Package Outlines(unit:mm)



SANYO Electric Co., Ltd. Semiconductor Business Headquarters. TR Division

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ON Semiconductor:

2SC4211-6-TL-E 2SC4211-7-TL-E