

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
J	-	D2		REVISED PER ECO-11-005030	11MAR11	RK	HMR

注記:  
 1. 使用端子型番は 170359,170360,170361,170362  
 2. 相手ハウジング型番は 172166  
 3. 適用パネル板厚: 0.8~2.0mm  
 4. 取付穴打抜方向とハウジングの挿入方向は同じとする。  
 5. 適用製品仕様書: 108-5138  
 6. 取扱説明書: IS-105J

NOTE  
 1. APPLICABLE CONTACT P/N: 170359,170360,170361,170362  
 2. MATING HOUSING P/N: 172166  
 3. APPLICABLE PANEL THICKNESS: 0.8~2.0mm  
 4. DIRECTION OF HOLE PUNCHING MUST BE SAME WITH HOUSING INSERTION DIRECTION.  
 5. APPLICABLE PRODUCT SPECIFICATION NO. : 108-5138  
 6. INSTRUCTION MANUAL: IS-105J

7. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

DIMENSION TOLERANCE IS ±0.20  
 寸法公差は ±0.20

APPLICABLE PANEL HOLE  
 パネル取付穴

OBSOLETE

BLACK 黒	1-172158-9
BLUE 青	1- -6
GREEN 緑	1- -5
RED 赤	1- -2
NATURAL 自然色	172158-1
COLOR 色	PART NUMBER 部品番号

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S.INOMATA 21AUG06	TE Connectivity	
DIMENSIONS: 単位: 純 mm		CHK N.YAMASAKI 21AUG06	NAME 名義	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差		APVD N.YAMASAKI 21AUG06	PRODUCT SPEC 製品規格 108-5138	
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		APPLICATION SPEC 取付適用規格	SIZE A2	CAGE CODE 00779
MATERIAL 材料 66NYLON(UL94V-0) 66ナイロン(UL94V-0)	FINISH 仕上	WEIGHT -	DRAWING NO 番号 C=172158	RESTRICTED TO -
CUSTOMER DRAWING			SCALE 尺度 4:1	SHEET 1 of 1

1471-9 (3/11)

172158

A