



Product: <u>9259</u> ☑

75 Ohm Analog Video Coax, RG-59, 22 AWG Str BC, 95% BC Braid, PVC Jkt, CM

Product Description

75 Ohm Analog Video Coax, RG-59, 22 AWG (7x30) Bare Copper Conductor , PE Insulation, 95% Bare Copper Braid Shield, PVC Jacket, CM

Technical Specifications

Product Overview

Suitable Ap	plications:	Standard analog video
Construc	tion Details	
	cton Details	
RG Type:		59
Conductor		
AWG Stra	nding Nom. Diame	eter Material
22 7x30	0.029 in	BC - Bare Copper
Insulation		
	terial Nom	n. Diameter
	hylene (Foam) 0.14	
Outer Shield	d Material	
Outer Shie	ld Type Materi	al Coverage
Braid	Bare Coppe	er (BC) 95%
Outer Jacke	t Material	
		Diameter
PVC - Polyv	/inyl Chloride 0.240	in
Electrica	I Characteristic	25
Attenuation		
Frequency		IdB/100ff1
1 MHz	0.3 dB/100ft	
5 MHz	0.65 dB/100ft	
10 MHz	0.9 dB/100ft	
50 MHz	2.1 dB/100ft	
100 MHz	3 dB/100ft	
200 MHz	4.5 dB/100ft	
400 MHz	6.6 dB/100ft	
700 MHz	8.9 dB/100ft	
900 MHz	10.1 dB/100ft	
1000 MHz	10.9 dB/100ft	

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Impedence	Nom. Velocity
15 Ohm/1000ft	2.6 Ohm/1000ft	17.3 pF/ft	75 Ohm	78%

300 V (CM), 30 V (UL AWM 1354)

Mechanical Characteristics

Temperature

Operating
-30°C to +75°C

......

Bend Radius

Installation Min.	
2.4 in	
Bulk Cable Weight:	34 lbs/1000ft
Max. Pull Tension:	52 lbs

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor
Sustainability:	CA Prop 65
Flammability / Fire Resistance:	UL1685 UL Loading
NEC / UL Compliance:	CM
AWM Compliance:	1354
CEC / C(UL) Compliance:	СМ
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	89259 or 82259

History

Update and Revision:

Revision Number: 0.313 Revision Date: 09-30-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.