






| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 2 1/4-16UN-2A     |
| B1  | 31.8              |
| B2  | 26.8              |
| C   | 22.2              |
| D   | 4                 |
| E   | 76                |
| F   | 63.1              |
| G   | 57.5              |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3   | DICHTKÖRPER / GROMMET               |
| 4   | ENDRING / ENDRING                   |
| 5   | KONTAKTSTIFT / CONTACT PIN          |
| 8   | DOSENGEHÄUSE / SHELL                |
| 12  | ENDGEHÄUSE / ENDBELL                |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.

Specification and Dimensions subject to change  
Drawings illustrate normal insulator positioning

|                                                                 |
|-----------------------------------------------------------------|
| <b>Material Specification:</b>                                  |
| Shell Material: Aluminium alloy                                 |
| Shell Plating: Olive drab chromate coating over cadmium plating |
| Insulator Material: Neoprene                                    |
| Contact Material: Copper alloy                                  |
| Contact Plating: Gold 0,5 & #956;                               |

all dimensions are in mm  
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
CUSTOMER



description  
CA3101E36-10P-A176  
Cable connecting plug  
Endbell with clamp and bushing  
Solder Cup / Pin / Layout: 36-10

© All rights reserved. Reproduction or issue to third in any form  
whatever is only permitted with written authorization of ITT Cannon



page  
1/1  
revision  
1041 28. Oct 20