

Single Supply, Rail-to-Rail Output Quad Operational Amplifier

■GENERAL DESCRIPTION

NJM2747 is a low noise Rail-to-Rail Output quad operational amplifier.

Rail-to-Rail Output function provides wide dynamic range, is from ground to power supply level. And Input range rails from ground level.

It is suitable for audio section of portable sets, PCs and any General-purpose applications.


NJM2747SCC is available in the small PCSP package, which saves space on printed circuit boards and suitable for small portable devices.

■FEATURES


- Operating Voltage 2.5V to 14V
- Rail-to-Rail Output $V_{OH} \geq 4.9V$ Typ. (at $V^+=5V$, $R_L=5k\Omega$)
 $V_{OL} \leq 0.1V$ Typ. (at $V^+=5V$, $R_L=5k\Omega$)
- Offset Voltage 1mV Typ.
- Slew Rate 3.5V/ μs Typ.
- Low Distortion 0.001% Typ. (at $V^+=5V$, $f=1kHz$)
- Low Input Voltage Noise 10nV/ $\sqrt{Hz}$ Typ. (at $f=1kHz$)
- Bipolar Technology
- Package Outline

NJM2747D	DIP14 (Lead insertion type)
NJM2747M	DMP14 (Surface mount type)
NJM2747V	SSOP14 (Surface mount type)
NJM2747SCC	PCSP20-CC (Surface mount type very small size package)

■PACKAGE OUTLINE



NJM2747D



NJM2747M



NJM2747V




NJM2747SCC


NJM2747

■ PIN CONFIGURATION

● NJM2747D, NJM2747M, NJM2747V



● NJM2747SCC



(Note1) The NC pin and the PAD should connect with a GND terminal.

(Note2) The NC pin is electrically not connected to the die in a package.

(Note3) The PAD is electrically not connected to the backside of the die. The PAD cannot be used as GND pin.

(Note4) NJM2747SCC package size is [W: 2.7mm, D: 2.7mm, H: 0.8mm]. Please confirm the size information by a package specification.

■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V^+	15	V
Differential Input Voltage Range	V_{ID}	± 15 (Note5)	V
Common Mode Input Voltage Range	V_{ICM}	0 to 15 (Note5)	V
Power Dissipation	P_D	870 [DIP14]	mW
		450 [DMP14] (Note6), 420 [SSOP14] (Note6), 380 [PCSP20-CC] (Note6),	
		560 [DMP14] (Note7), 520 [SSOP14] (Note7), 550 [PCSP20-CC] (Note7),	
Operating Temperature Range	T_{opr}	-40 to +85	°C
Storage Temperature Range	T_{stg}	-50 to +125	°C

(Note5) For supply voltage less than 15V, the absolute maximum input voltage is equal to the supply voltage.

(Note6) On the PCB "EIA/JEDEC (76.2×114.3×1.6mm, two layers, FR-4)"

(Note7) On the PCB "EIA/JEDEC (76.2×114.3×1.6mm, four layers, FR-4)"

(Note8) Do not exceed "Power dissipation: PD" in which power dissipation in IC is shown by the absolute maximum rating.

Refer to following Figure 1A and Figure 1B for a permissible loss when ambient temperature (T_a) is $T_a \geq 25^\circ\text{C}$.

Figure 1A : Power Dissipation – Ambient Temperature





Figure 1B : Power Dissipation – Ambient Temperature



■ OPERATING VOLTAGE ($T_a=25^\circ\text{C}$)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V^+	2.5 to 14 (Note8)	V

■ ELECTRICAL CHARACTERISTICS

●DC CHARACTERISTICS ($V^+=5V, T_a=25^\circ C$)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Operating Current	I_{CC}	$R_L=\infty, V_{IN}=2.5V$, No Signal Apply	-	8	11	mA
Input Offset Voltage	V_{IO}	$R_S \leq 10k\Omega$	-	1	6	mV
Input Bias Current	I_B		-	100	350	nA
Input Offset Current	I_{IO}		-	5	100	nA
Large Signal Voltage Gain	A_V	$R_L \geq 10k\Omega$ to 2.5V, $V_O=0.5V$ to 4.5V	65	85	-	dB
Common Mode Rejection Ratio	CMR	$0V \leq V_{CM} \leq 4V$	60	75	-	dB
Supply Voltage Rejection Ratio	SVR	$V^+=2.5V$ to 14V	60	80	-	dB
Output Voltage	V_{OH}	$R_L=5k\Omega$ to 2.5V	4.75	4.9	-	V
	V_{OL}	$R_L=5k\Omega$ to 2.5V	-	0.1	0.25	V
Input Common Mode Voltage Range	V_{ICM}	CMR $\geq 60dB$	0	-	4	V

●AC CHARACTERISTICS ($V^+=5V, T_a=25^\circ C$)






PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Unity Gain Bandwidth	GB	$f=10kHz$	-	10	-	MHz
Phase Margin	Φ_M	$R_L=10k\Omega, C_L=10pF$	-	75	-	Deg
Equivalent Input Noise Voltage	V_{NI}	$f=1kHz, V_{CM}=2.5V$	-	10	-	nV/ $\sqrt{Hz}$
Total Harmonic Distortion	THD	$f=1kHz, A_V=+2$ $R_L=10k\Omega$ to 2.5V, $V_O=1.5V_{rms}$	-	0.001	-	%
Amp to Amp Separation	CS	$f=1kHz$ $R_L=10k\Omega$ to 2.5V, $V_O=1.5V_{rms}$	-	120	-	dB

●AC CHARACTERISTICS ($V^+=5V, T_a=25^\circ C$)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Slew Rate	SR	(Note 9), $A_V=1, V_{IN}=2V_{pp}$ $R_L=10k\Omega$ to 2.5V $C_L=10pF$ to 2.5V	-	3.5	-	V/ μs


(Note 9) Number specified is the slower of the positive and negative slew rates.

■ TYPICAL CHARACTERISTICS




■ TYPICAL CHARACTERISTICS


Input Bias Current vs. Ambient Temperature
(Supply Voltage)
 $R_L = 10k\Omega$




Input Offset Current vs. Ambient Temperature (Supply Voltage)
 $R_L = 10k\Omega$




Maximum Output Voltage vs. Supply Voltage
(Temperature, $R_L = 10k\Omega$)
 $G_V = OPEN$, $R_L = 10k\Omega$




Maximum Output Voltage vs. Supply Voltage
(Temperature, $R_L = 5k\Omega$)
 $G_V = OPEN$, $R_L = 10k\Omega$







Maximum Output Voltage vs. Load Resistance
(Temperature, $V^+ = 5V$)
 $V^+ = 5V$, $G_V = OPEN$








Maximum Output Voltage vs. Output Current
(Temperature, $V^+ = 5V$)
 $V^+ = 5V$, $G_V = OPEN$



■ TYPICAL CHARACTERISTICS




■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS


THD+N vs. Output Voltage (Frequency)

$V^+=5V$, $A_v=+2$, $R_S=600\Omega$, $R_F=5k\Omega$, $R_G=5k\Omega$,
 $BW=10Hz\sim80kHz$, $T_a=25^\circ C$




THD+N vs. Output Voltage (Supply Voltage)

$f=1kHz$, $A_v=+2$, $R_S=600\Omega$, $R_F=5k\Omega$, $R_G=5k\Omega$,
 $BW=10Hz\sim80kHz$, $T_a=25^\circ C$




Equivalent Input Noise Voltage
 vs. Frequency (Supply Voltage)

$G_v=60dB$, $R_i=600\Omega$, $R_F=100k\Omega$, $R_G=100\Omega$, $T_a=25^\circ C$




Channel Separation vs. Frequency

$V^+=5V$, Ach Input, $V_O=1.5Vrms$, $G_v=40dB$, $R_F=100k\Omega$,
 $R_G=1k\Omega$, $R_i=10k\Omega$, $T_a=25^\circ C$



Channel Separation vs. Frequency

$V^+=5V$, Cch Input, $V_O=1.5Vrms$, $G_v=40dB$, $R_F=100k\Omega$,
 $R_G=1k\Omega$, $R_i=10k\Omega$, $T_a=25^\circ C$



■ MEMO

[CAUTION]
The specifications on this data book are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this data book are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[NJR:](#)

[NJM2747V-TE2](#) [NJM2747M-TE1](#) [NJM2747D](#) [NJM2747SCC-TE1](#) [NJM2747V-TE1](#)