

RM Cores (6295370121)

Part Number: 6295370121

95 RM CORE SET

RM (Rectangular Modulus) cores allow better shielding than E type geometries while also providing easier winding accessibility and better power dissipation than a pot core configuration. Fair-Rite's standard RM cores all have a solid center post and standard height, low profile and alternate materials are available upon request.

RM cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

[Catalog Drawing](#)

[3D Model](#)

Weight indicated is per pair or set.

Weight: 46 (g)

| Dim | mm | mm tol | nominal inch | inch misc. |
|-----|-------|--------|--------------|------------|
| A | 36.75 | ± 0.75 | 1.447 | — |
| B | 12.25 | ± 0.15 | 0.482 | — |
| C | 15.85 | ± 0.25 | 0.624 | — |
| D | 8.55 | ± 0.20 | 0.337 | — |
| E | 25.45 | ± 0.55 | 1.002 | — |
| F | 12.6 | ± 0.20 | 0.496 | — |
| G | 13.4 | min | 0.528 | min |
| J | 29.2 | ± 0.60 | 1.15 | — |



Figure 1

Chart Legend

$\Sigma l / A$: Core Constant, l_e : Effective Path Length, A_e : Effective Cross- Sectional Area, V_e : Effective Core Volume

A_L : Inductance Factor 

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

| Electrical Properties | |
|------------------------------------|-----------|
| A_L (nH) | 6360 ±25% |
| A_e (cm ²) | 1.41 |
| $\Sigma l / A$ (cm ⁻¹) | 4.3 |
| l_e (cm) | 6.13 |
| V_e (cm ³) | 8.675 |
| A_{min} (cm ²) | 1.247 |

A_L value is measured at 1 kHz, B < 10 gauss.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Fair-Rite:](#)

[6295370121](#)