

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

—, — .

© COPYRIGHT — By —

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

—

—

P

LTR

DESCRIPTION

DATE

DWN

APVD

G1

REVISED PER ECO-11-020548

02FEB12

KH

DR

1

FOR 2.67[.105] TO 3.56[.140] WIRE INSULATION DIA

INSULATION

SERRATIONS

BODY

AMP

AMP

AMP

AMP

27.05

[1.065]

MAX

WIRE STOP

100	LOOSE PC/BOX	INSULATION: PVC COLOR: BLUE BODY: COPPER PER ASTM B152 TIN PLATE PER ASTM B545	8-34068-1
2500	34068 ON TAPE		2-34068-1
1000	LOOSE PIECE		34068
QTY	PACKAGE TYPE	MATERIAL & FINISH	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± 0.20[.008]

4 PLC ± -

ANGLES ± 5°

MATERIAL

-

FINISH

-

DWN
KIRAN HOLAL
CHK
ROHDE DANIEL
APVD
ROHDE DANIEL

02FEB12
02FEB12
02FEB12

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

-

STE

TE Connectivity

NAME

WIRE SPLICE PLASTI GRIP, BUTT, WIRE SIZE: 16-14

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-34068

-

CUSTOMER DRAWING

SCALE 8:1

SHEET 1 OF 1

REV G1

1470-19

(3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[34068](#)