



LOC		DIST		REVISIONS			
P	LTR	DESCRIPTION		DATE	DWN	APVD	
	C	REVISED PER ECR-16-003247		14JUL2016	BW	GJ	


D





C



B



A



C

B









A

- ⚠ MATERIAL:
LEVEL 1:PBT, STANDARD TEMPERATURE 105°C.
KEY A:NATURAL; KEY B:PURPLE; KEY C:BLUE; KEY D:YELLOW
- LEVEL 2:NYLON, HIGH TEMPERATURE 150°C
KEY A:LIGHT GREY; KEY B:RED; KEY C:BLACK; KEY D:NATURAL
- 2 MATERIAL MARK:
LEVEL 1:PBT, LEVEL 2:HDT
- 3 APPLICABLE CONTACT P/N
TAB CONTACT:1971238/1971780/82/84/86/88-*,2238067-*
- 4 MATING CONN, P/N
PLUG HSG: *-1971773-
TPA (LOCK PLATE): *-1971777-*
- 5 THIS DRAWING DOES NOT PERTAIN TO RESTRICTED P/N 5-1971771-2.
- 6 THIS PRODUCT HAS NOT COMPLETED VALIDATION TESTING



POS.	DIM.A	DIM.B	DIM.C
1*5	33.70	27.50	31.30
1*4	27.70	21.50	25.30
1*3	21.70	15.50	19.30
1*2	15.70	9.50	13.30

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN TOMMY.WU 09JUL2012	TE Connectivity	
		CHK HAPYE.WU 09JUL2012		
DIMENSIONS:		APVD YUHONG.MAO 09JUL2012	NAME CAP HOUSING,FREE HANGING,SINGLE ROW POWER TRIPLE LOCK	
mm		PRODUCT SPEC		
		108-106118	SIZE CAGE CODE DRAWING NO	
		APPLICATION SPEC		
MATERIAL		114-106118	A100779C=1971771	
		FINISH		
		WEIGHT	Customer Drawing	
			SCALE	SHEET 1 OF 2
				REV C

LOC		DIST		REVISIONS					
-		-		P	LTR	DESCRIPTION	DATE	DWN	APVD
				-	-	SEE SHEET 1	-	-	-





1*2 POSITIONS





KEYING FOR 1*2 POS.

1*3 POSITIONS





KEYING FOR 1*3 POS.

1*4 POSITIONS



KEYING FOR 1*4 POS.

1*5 POSITIONS



KEYING FOR 1*5 POS.

1*5	LEVEL 1	KEY A	1-1971771-7
		KEY B	2-1971771-7
		KEY C	3-1971771-7
		KEY D	4-1971771-7
	LEVEL 2	KEY A	5-1971771-7
		KEY B	6-1971771-7
		KEY C	7-1971771-7
		KEY D	8-1971771-7
1*4	LEVEL 1	KEY A	1-1971771-4
		KEY B	2-1971771-4
		KEY C	3-1971771-4
		KEY D	4-1971771-4
	LEVEL 2	KEY A	5-1971771-4
		KEY B	6-1971771-4
		KEY C	7-1971771-4
		KEY D	8-1971771-4
POS.	MATERIAL	KEY	P/N

1*3	LEVEL 1	KEY A	1-1971771-3
		KEY B	2-1971771-3
		KEY C	3-1971771-3
		KEY D	4-1971771-3
	LEVEL 2	KEY A	5-1971771-3
		KEY B	6-1971771-3
		KEY C	7-1971771-3
		KEY D	8-1971771-3
1*2	LEVEL 1	KEY A	1-1971771-2
		KEY B	2-1971771-2
		KEY C	3-1971771-2
		KEY D	4-1971771-2
	LEVEL 2	KEY A	9-1971771-2
		KEY B	6-1971771-2
		KEY C	7-1971771-2
		KEY D	8-1971771-2
POS.	MATERIAL	KEY	P/N

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
TOMMY_WU
09JUL2012

CHK
HAPYE_WU
09JUL2012

APVD
YUJHONG_MAO
09JUL2012

DIMENSIONS:

mm

0 PLC ±.35
1 PLC ±0.25
2 PLC ±.25
3 PLC ±.
4 PLC ±.
ANGLES ±.
FINISH -

TOLERANCES UNLESS OTHERWISE SPECIFIED:

PRODUCT SPEC
108-106118
APPLICATION SPEC
114-106118
WEIGHT -

Customer Drawing

SCALE -

SHEET 2 OF 2

REV C

TE Connectivity

NAME
CAP HOUSING,FREE HANGING,SINGLE ROW
POWER TRIPLE LOCK

SIZE
A100779

CAGE CODE
C=1971771

DRAWING NO
1971771

RESTRICTED TO

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5-1971771-7](#)