





REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	P3	REVISED PER ECO-11-004587	11MAR11	RK	HMR
	R	REVISED PER ECO-17-002583	08APR2017	RS	MM



RECOMMENDED HOLE LAYOUT

- 1 HOUSING: FLAME RETARDANT, LCP, BLACK
POST: BRASS
- 2 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 3 THE NOTED DIMENSIONS APPLY FROM THE BASIC
DIMENSION LINE (NOT THE POST CENTERLINE)
TO THE SURFACE INDICATED
- 4 ON ASSEMBLIES WITH FOUR OR MORE POSITIONS,
TWO POLARIZATION SLOTS.
ON ASSEMBLIES WITH TWO OR THREE POSITIONS,
ONE POLARIZATION SLOT.
- 5 FOR USE WITH .062±008 PRINTED CIRCUIT BOARD
- 6 .000030 GOLD IN THE CONTACT AREA,
.000100-.000200 MATTE TIN-LEAD ON THE
SOLDER TAIL, ALL OVER .000050 NICKEL
- 7 .000030 GOLD IN THE CONTACT AREA,
.000100-.000200 MATTE TIN ON THE
SOLDER TAIL, ALL OVER .000050 NICKEL
- 8 HIGH TEMPERATURE CONFIGURATION.
- 9 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING

OBSOLETE 9	8	7	2.595	2.520	2.400	24	25	7-103904-4			
			2.495	2.420	2.300	23	24	7-103904-3			
			2.395	2.320	2.200	22	23	7-103904-2			
			2.295	2.220	2.100	21	22	7-103904-1			
2.195			2.120	2.000	20	21	7-103904-0				
2.095			2.020	1.900	19	20	6-103904-9				
1.995			1.920	1.800	18	19	6-103904-8				
1.895			1.820	1.700	17	18	6-103904-7				
1.795			1.720	1.600	16	17	6-103904-6				
1.695			1.620	1.500	15	16	6-103904-5				
1.595			1.520	1.400	14	15	6-103904-4				
1.495			1.420	1.300	13	14	6-103904-3				
1.395			1.320	1.200	12	13	6-103904-2				
1.295			1.220	1.100	11	12	6-103904-1				
1.195			1.120	1.000	10	11	6-103904-0				
1.095			1.020	.900	9	10	5-103904-9				
.995			.920	.800	8	9	5-103904-8				
.895			.820	.700	7	8	5-103904-7				
.795			.720	.600	6	7	5-103904-6				
.695			.620	.500	5	6	5-103904-5				
.595			.520	.400	4	5	5-103904-4				
.495			.420	.300	3	4	5-103904-3				
.395			.320	.200	2	3	5-103904-2				
.295			.220	.100	1	2	5-103904-1				
9 OBSOLETE			8	6	2.595	2.520	2.400	24	25	2-103904-4	
9 OBSOLETE					2.495	2.420	2.300	23	24	2-103904-3	
9 OBSOLETE					2.395	2.320	2.200	22	23	2-103904-2	
9 OBSOLETE					2.295	2.220	2.100	21	22	2-103904-1	
9 OBSOLETE					2.195	2.120	2.000	20	21	2-103904-0	
9 OBSOLETE					2.095	2.020	1.900	19	20	1-103904-9	
9 OBSOLETE	1.995	1.920			1.800	18	19	1-103904-8			
9 OBSOLETE	1.895	1.820			1.700	17	18	1-103904-7			
9 OBSOLETE	1.795	1.720			1.600	16	17	1-103904-6			
9 OBSOLETE	1.695	1.620			1.500	15	16	1-103904-5			
9 OBSOLETE	1.595	1.520			1.400	14	15	1-103904-4			
9 OBSOLETE	1.495	1.420			1.300	13	14	1-103904-3			
9 OBSOLETE	1.395	1.320			1.200	12	13	1-103904-2			
9 OBSOLETE	1.295	1.220			1.100	11	12	1-103904-1			
9 OBSOLETE	1.195	1.120			1.000	10	11	1-103904-0			
9 OBSOLETE	1.095	1.020			.900	9	10	103904-9			
9 OBSOLETE	.995	.920			.800	8	9	103904-8			
9 OBSOLETE	.895	.820			.700	7	8	103904-7			
9 OBSOLETE	.795	.720			.600	6	7	103904-6			
9 OBSOLETE	.695	.620			.500	5	6	103904-5			
9 OBSOLETE	.595	.520			.400	4	5	103904-4			
9 OBSOLETE	.495	.420			.300	3	4	103904-3			
9 OBSOLETE	.395	.320			.200	2	3	103904-2			
9 OBSOLETE	.295	.220			.100	1	2	103904-1			
6-103904-2	8	6									

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN 5-17-93 E. BRANDBERG OK: J. GESFORD 5-17-93		 TE Connectivity	
DIMENSIONS: INCHES		TOLERANCES, UNLESS OTHERWISE SPECIFIED: 0 PLC ± .— 1 PLC ± .— 2 PLC ± .— 3 PLC ± .005 4 PLC ± .— ANGLES ± .—		NAME HEADER ASSY, AMPMODU MTE, RIGHT ANGLE, SINGLE ROW, 100CL .025 SQ POSTS, WITH LATCH & HOLD DOWNS	
		APVD — PRODUCT SPEC 108-25034 APPLICATION SPEC —		SIZE CAGE CODE DRAWING NO A1 00779	
MATERIAL 		FINISH SEE TABLE		RESTRICTED TO —	
CUSTOMER DRAWING				SCALE 4:1 SHEET 1 OF 1 REV R	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[103904-4](#)