



**FEATURES:**

- Permits banana plug cords to be used with equipment having pin tip jacks.

**MATERIALS:**

Upper Conn.: Banana Jack

Material: Brass rod per ASTM B16-85, Temper H02.

Finish: Nickel plated per QQ-N-290, Class 2, 200/300 micro-inches.

Insulation: ABS molded to banana jack and pin tip body.

Marking: "1432 POMONA ELECTRONICS CALIF."

Lower Conn.: Pin Tip Plug

Material: Brass rod per ASTM B16-85, Temper H02.

Finish: Nickel plated per QQ-N-290, Class 2, 200/300 micro-inches.

**RATINGS:**

Operating Temperature: +50°C. (+122°F.) Max.

Operating Voltage: 3000 VDC.

Current: 5 Amperes

**ORDERING INFORMATION:** Model 1432-\*

\*= Color, -0 Black, -2 Red. Ordering Example: 1432-2 Adapter Color is Red

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

[1432-0](#) [1432-2](#)