


REV. 0  
DCO 141918

|                      |                            |
|----------------------|----------------------------|
| COIL: @ 25°C         |                            |
| RESISTANCE           | 125 OHMS ±10%              |
| NOMINAL VOLTAGE      | 5.0 VDC                    |
| MUST OPERATE         | 2.6 VDC                    |
| TURN-ON BASE CURRENT | .28 mA DC                  |
| MUST RELEASE         | 1.4 VDC MAX, 0.22 VDC MIN. |

|              |                                       |
|--------------|---------------------------------------|
| ENVIRONMENT: |                                       |
| VIBRATION    | 10 CPS TO 3000 CPS @ 30 g's           |
| SHOCK        | 75 g's 6 MS. DURATION                 |
| TEMPERATURE  | -65 °C TO +125 °C                     |
| NOTES:       | TURN-ON TIME 3.5 MS MAX               |
|              | TURN-OFF TIME 7.5 MS MAX              |
|              | CONTACT STABILIZATION TIME 2.0 MS MAX |

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: LOW LEVEL TO 1A  
28 VDC RESISTIVE 100,000 OPERATIONS

DR. PBB 4-18-00 EK. *[Signature]* 9/24/00

COMMUNICATIONS  
INSTRUMENTS, INC.

CUST. QPL  
CUST. NO. M28776/4-017P REV.

RELAY

J1MSWT-5XP

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[J1MSWT-5XP](#)