

Type 4295 Series

Key Features

- High Resolution Cermet Element For Stability
- Enclosure Sealed
- 0.5 Watt Rating at 85°C
- Flame Retardant
- P.C.B. Standoffs
- Robust Construction
- Vertical or Horizontal Adjustments Available
- Finger Adjustment Available



These long established 10mm square, single turn potentiometers will meet a wide range of industrial and professional applications. Cermet element technology ensures stability and reliability. This P.C.B. mounted package has easy top or side adjustment, or finger adjust styles. All components are sealed to withstand printed circuit board washing solvents.

Characteristics - Electrical

| | |
|-----------------------------------|---------------------------------------|
| Resistance Range: | 100R to 2M |
| STD Resistance Values: | 2 and 5 in each decade |
| STD Resistance Tolerance: | ± 1% |
| End Resistance: | 10 Ohms or 1% whichever is greater |
| Slider Current: | 100 mA or within power rating, Max. |
| Power Rating: | 0.5 at 85°C derating to zero at 125°C |
| Isolation Voltage: | 300 V dc or ac peak |
| Limiting Element Voltage: | 220 V dc or ac RMS, Max. |
| Breakdown Voltage (Solder Level): | 900 V ac for one minute |
| Insulation Resistance: | 1000 M Ohms at 500 V dc, Min. |
| Dielectric Absorption: | Essentially Infinite |
| Rotational Noise (CRV): | 3 Ohms or 2 % min. |
| Temperature Coefficient: | ± 250 ppm/°C, Max. |
| Electrical Adjustment: | 280° Nominal |

Characteristics - Mechanical

| | |
|------------------------|-------------------------|
| End Stop: | 40 mNm Min. |
| Starting Torque: | 35 mNm Max. |
| Mechanical Adjustment: | 300° Nominal |
| Weight: | 0.85 gm Nominal |
| Solderability: | MIL Std 202 Method 208A |

Type 4295 Series

Characteristics - Environmental

| | |
|----------------------|---|
| Temperature Range: | -55°C to +125°C |
| Temperature Storage: | 250 Hrs at 125°C |
| Thermal Shock: | 5 Cycles -55°C to +125°C |
| Bump Severity: | 4000 Bumps; 40G |
| Vibration Severity: | 10 - 500Hz; 30 G |
| Rotational Life: | 200 Cycles, Min. |
| Load Life at 70°C: | $\Delta R < 3\%$ after 1000 Hrs. at 0.5 watts |
| Sealing: | Sealed for board washing (85°C Florinert) |
| Climatic Category: | 55/125/56 |
| Humidity: | MIL - Std - 202G Method 103 (96hrs) |

Dimensions - 4295P



Type 4295 Series

Dimensions - 4295MF/PF



How to Order

| | | | |
|--------------------|---|---|------------------|
| 4295 | P | 104 | K |
| Common Part | Pin Configuration | Resistance Value | Tolerance |
| 4295 | <ul style="list-style-type: none"> Top Adjust 8mm x 5mm MF - Finger Top Adjust 8mm x 5mm P - Top Adjust 8mm x 2.5mm PF - Finger Top Adjust 8mm x 2.5mm X - Side Adjust 8mm x 2.5mm | <p>The first two digits are significant figures of resistance value and the third denotes the number of zeros following.</p> <p>e.g. 100R: 101 1K: 102 10K: 103 100K: 104</p> | K - 10% |

OBSOLETE

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[404806391011](#)