

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0740601001

Status:

Active

Overview:

VHDM Backplane Connector Systems

Description:

VHDM Single-Ended Board-to-Board Backplane Header, 2.00mm Pitch, Vertical, 8 Rows, Open Signal Module, 80 Circuits, 10 Columns, Pin Length 4.75mm

Documents:

3D Model

Packaging Specification PK-74060-003 (PDF)

Drawing (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

UL

E29179

General

Product Family

Backplane Connectors

Series

74060

Application

Backplane

Application Tooling Documents

TM-622010999

Comments

Open Header

Component Type

PCB Header

Overview

VHDM Backplane Connector Systems

Product Name

VHDM

UPC

800754780872

Physical

Circuits (Loaded)

80

Circuits (maximum)

80

Color - Resin

Black

Durability (mating cycles max)

200

First Mate / Last Break

No

Flammability

94V-0

Guide to Mating Part

No

Keying to Mating Part

None

Material - Metal

Beryllium Copper, High Performance Alloy (HPA)

Material - Plating Mating

Gold

Material - Plating Termination

Matte Tin

Material - Resin

High Temperature Thermoplastic

Net Weight

5.687/g

Number of Columns

10

Number of Pairs

Open Pin Field

Number of Rows

8

Orientation

Vertical

PC Tail Length

2.50mm

PCB Locator

No

PCB Retention

None

PCB Thickness - Recommended

1.80mm

Packaging Type

Tube

Pitch - Mating Interface

2.00mm

Pitch - Termination Interface

1.00mm

Plating min - Mating

0.762µm

Plating min - Termination

0.762µm

Polarized to PCB

Yes

Surface Mount Compatible (SMC)

Yes


Temperature Range - Operating

-55° to +105°C

Termination Interface: Style

Through Hole - Compliant Pin

Electrical



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

China RoHS

REACH SVHC

Not Contained Per -
ED/61/2018 (27 June
2018)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

Green Image

ELV

Not Relevant

RoHS Phthalates

Not Contained

Search Parts in this Series

74060 Series

Mates With

74040 VHDM Board-to-Board Daughtercard
Receptacle

Current - Maximum per Contact	3.0A
Data Rate	3.125 Gbps
Shield Type	Ground Plane Shield
Shielded	Yes
Voltage - Maximum	120V AC (RMS)/DC
Solder Process Data	
Lead-freeProcess Capability	N/A
Material Info	
Reference - Drawing Numbers	
Packaging Specification	PK-74060-003
Sales Drawing	SD-74060-002

This document was generated on 10/08/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[74060-1001](#)