

# XS130B3NBM12

inductive sensor XS1 M30 - L55mm - brass - Sn15mm - 12..24VDC - M12



Product availability: Stock - Normally stocked in distribution facility



## Main

|                                    |  |
|------------------------------------|--|
| Commercial Status                  | Commercialised   |
| Range of product                   | OsiSense XS  |
| Series name                        | General purpose  |
| Sensor type                        | Inductive proximity sensor                                   |
| Product specific application       | -  |
| Sensor name                        | XS1  |
| Sensor design                      | Cylindrical M30  |
| Size                               | 55 mm  |
| Body type                          | Fixed  |
| Detector flush mounting acceptance | Flush mountable  |
| Material                           | Metal  |
| Type of output signal              | Discrete   |
| Wiring technique                   | 3-wire   |
| [Sn] nominal sensing distance      | 0.59 in (15 mm)  |
| Discrete output function           | 1 NC   |
| Output circuit type                | DC   |
| Discrete output type               | NPN  |
| Electrical connection              | M12 male connector, 4 pins                                   |
| [Us] rated supply voltage          | 12...24 V DC with reverse polarity protection                |
| Switching capacity in mA           | <= 200 mA with overload and short-circuit protection         |
| IP degree of protection            | IP67 conforming to IEC 60529<br>IP65 conforming to IEC 60529 |
| Sale per indivisible quantity      | 1  |

## Complementary

|                       |                                 |
|-----------------------|---------------------------------|
| ISO thread            | M30 x 1.5                       |
| Detection face        | Frontal                         |
| Front material        | PPS                             |
| Enclosure material    | Nickel plated brass             |
| Operating zone        | 0...0.47 in (0...12 mm)         |
| Differential travel   | 1...15% of Sr                   |
| Status LED            | 1 LED (yellow) for output state |
| Supply voltage limits | 10...36 V DC                    |
| Switching frequency   | <= 500 Hz                       |
| Voltage drop          | <= 2 V (closed state)           |
| Current consumption   | <= 10 mA (no-load)              |
| Delay first up        | <= 10 ms                        |
| Delay response        | <= 0.6 ms                       |
| Delay recovery        | <= 1.4 ms                       |
| Marking               | CE                              |

|                 |                       |
|-----------------|-----------------------|
| Threaded length | 1.26 in (32 mm)       |
| Length          | 2.17 in (55 mm)       |
| Product weight  | 0.29 lb(US) (0.13 kg) |

## Environment

|                                       |   |
|---------------------------------------|---|
| Product certifications                | CSA<br>UL   |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)  |
| Ambient air temperature for storage   | -40...185 °F (-40...85 °C)  |
| Vibration resistance                  | 25 gn, amplitude: +/- 2 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance                      | 50 gn (duration = 11 ms) conforming to IEC 60068-2-27                   |

## Ordering and shipping details

|                       |   |
|-----------------------|---|
| Category              | 21571 - SENSORS, ELECTRONIC BASIC XU & XS         |
| Discount Schedule     | DS2   |
| GTIN                  | 00785901918479                                    |
| Nbr. of units in pkg. | 1   |
| Package weight(Lbs)   | 0.29  |
| Product availability  | Stock - Normally stocked in distribution facility |
| Returnability         | Y   |
| Country of origin     | FR  |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS                             | Compliant - since 0846 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Available <a href="#">Download End Of Life Manual</a>                                 |

## Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XS130B3NBM12](#)