

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** [0190030041](#)  
**Status:** **Active**  
**Overview:** [Standard Quick-Disconnect Terminals](#)  
**Description:** InsulKrimp Quick Disconnect, Female, for 14-16 (2.00-1.30mm<sup>2</sup>), Continuous Molded Strip, Tab 6.35 x 0.81mm

|                                |                                                              |
|--------------------------------|--------------------------------------------------------------|
| <b>Documents:</b>              |                                                              |
| <a href="#">3D Model</a>       | <a href="#">Product Specification PS-19902-008-001 (PDF)</a> |
| <a href="#">Drawing (PDF)</a>  | <a href="#">Product Specification PS-19902-011-001 (PDF)</a> |
| <a href="#">3D Model (PDF)</a> | <a href="#">RoHS Certificate of Compliance (PDF)</a>         |

**Agency Certification**

|     |         |
|-----|---------|
| CSA | LR18689 |
| UL  | E79133  |

**General**

|                         |                                                     |
|-------------------------|-----------------------------------------------------|
| Product Family          | Quick Disconnects                                   |
| Series                  | <a href="#">19003</a>                               |
| Comments                | Funnel Entry                                        |
| Crimp Quality Equipment | Yes                                                 |
| Insulated               | Fully                                               |
| Overview                | <a href="#">Standard Quick-Disconnect Terminals</a> |
| Product Name            | InsulKrimp                                          |
| Type                    | Quick Disconnect                                    |
| UPC                     | 800753029071                                        |

**Physical**


|                                |                      |
|--------------------------------|----------------------|
| Barrel Type                    | Closed               |
| Color - Resin                  | Blue                 |
| Flammability                   | 94V-2                |
| Gender                         | Female               |
| Glow-Wire Capable              | No                   |
| Insulation                     | Nylon (PA)           |
| Lock to Mating Part            | None                 |
| Material - Metal               | Brass                |
| Material - Plating Mating      | Tin                  |
| Material - Plating Termination | Tin                  |
| Material - Resin               | Nylon                |
| Net Weight                     | 0.990/g              |
| Orientation                    | Straight             |
| Packaging Type                 | Reel                 |
| Plating min - Mating           | 4.064µm              |
| Plating min - Termination      | 4.064µm              |
| Polarized to Mating Part       | No                   |
| Tab Thickness                  | 0.81mm               |
| Tab Width                      | 6.35mm               |
| Temperature Range - Operating  | -65° to +105°C       |
| Termination Interface: Style   | Crimp or Compression |
| Wire Insulation Diameter       | 3.68mm max.          |
| Wire Size AWG                  | 14, 16               |
| Wire Size mm <sup>2</sup>      | 1.30-2.00            |

**Electrical**

|                   |      |
|-------------------|------|
| Voltage - Maximum | 600V |
|-------------------|------|

**Solder Process Data**

|                             |     |
|-----------------------------|-----|
| Lead-freeProcess Capability | N/A |
|-----------------------------|-----|



Series image - Reference only

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
ECHA\_01\_2020 (16  
January 2020

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

|                 |               |
|-----------------|---------------|
| China ROHS      | Green Image   |
| ELV             | Not Relevant  |
| RoHS Phthalates | Not Contained |

**Search Parts in this Series**

[19003 Series](#)

**Application Tooling | [FAQ](#)**

*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*

**Global**

| Description         | Product #                 |
|---------------------|---------------------------|
| Mini-Mac Applicator | <a href="#">638834200</a> |

**Material Info**

Engineering Number BB-2206C

**Reference - Drawing Numbers**

Product Specification PS-19902-008-001, PS-19902-011-001  
Sales Drawing SD-19003-005-001

This document was generated on 04/13/2020

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

19003-0041