

Toggle Switches

| RATINGS | CIRCUIT | TOGGLE POSITION | | | CATALOG NUMBER | | | |
|---------|---------|-----------------|--------|------------------|---------------------|-------|--------------|---------------|
| | | | | | TYPE OF TERMINATION | | | |
| | | UP | CENTER | DOWN (keyway) | .187 Q.C. | SCREW | .250 Q.C. | SOLDER LUG |

9100 SERIES TOGGLE

| 6A-125VAC 3A-250VAC | DPST | ON | NONE | OFF | 9103A | 9103B | 9103C | 9103D |
|------------------------|------|----|------|-----|-------|-------|-------|-------|
| | DPDT | ON | NONE | ON | 9101A | 9101B | 9101C | 9101D |
| | | ON | OFF | ON | 9102A | 9102B | 9102C | 9102D |

9000 SERIES TOGGLE

| 15A-125VAC 10A-250VAC | DPST | ON | NONE | OFF | 9003A | 9003B | 9003C | 9003D |
|--------------------------|------|----|------|-----|-------|-------|-------|-------|
| | DPDT | ON | NONE | ON | 9001A | 9001B | 9001C | 9001D |
| | | ON | OFF | ON | 9002A | 9002B | 9002C | 9002D |

9200 SERIES TOGGLE

| 20A-125VAC 10A-250VAC 3/4 HP, 125-250VAC | DPST | ON | NONE | OFF | 9203A | 9203B | 9203C | 9203D |
|---|------|----|------|-----|-------|-------|-------|-------|
| | DPDT | ON | NONE | ON | 9201A | 9201B | 9201C | 9201D |
| | | ON | OFF | ON | 9202A | 9202B | 9202C | 9202D |

For .687 Toggle And .468 Bushing Length Add-100 To Part Number Specified
For Dust And Moisture Resistant Seal Add "S" To Part Number Specified

SPECIFICATIONS

Agency Listings

 CSA Certified

Contact Mechanism

Slow-Make/Slow-Break Butt Contact

Contact Material

9100 Series:

Stationary - Copper Alloy/Silver Plated

Movable - Copper Alloy

9000 And 9200 Series:

Stationary (Center) - Copper Alloy/Silver Plated

Stationary (End) - Silver Cadmium Oxide Composite

Movable-Silver Cadmium Oxide Composite

Dielectric Strength

1000 Volts RMS Minimum

Mounting Means


15/32" Diameter Threaded Bushing

Keyway .078-.083 Wide X .037-.043 Deep

Standard Hardware Supplied —

One Hex Nut Assembled And

One Hex Nut Unassembled.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Electroswitch:](#)

[9201C](#) [9202C](#) [9203C](#) [9003D](#)