

Cable ring - SAC-8P-100,0-PVC/SH-0,25 - 1550708

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable ring, PVC, black, 8-pos. shielded, conductor colors: White / brown / green / yellow / gray / pink / blue / red, cable length: 100 m



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	8820.0 g
Custom tariff number	85444995
Country of origin	Germany

Technical data

Dimensions

Length of cable	100 m
-----------------	-------

General

Number of positions	8
---------------------	---

Cable

Note	The cable is not suitable for use with drag chains.
Cable type	PVC black
Cable type (abbreviation)	PVC
Cable abbreviation	LiYF-C-Y
Conductor cross section	8x 0.25 mm ² (Signal line)
AWG signal line	24
Conductor structure signal line	32x 0.10 mm
Core diameter including insulation	1.5 mm ±0.05 mm (Signal line)
Thickness, insulation	≥ 0.38 mm (Conductor insulation, signal line)
	≥ 0.76 mm (Outer cable sheath)
Wire colors	white, brown, green, yellow, gray, pink, blue, red

Cable ring - SAC-8P-100,0-PVC/SH-0,25 - 1550708

Technical data

Cable

Overall twist	8 wires around filler to the core, twisted in with additional Cu litz in the wire outer godet
Shielding	Tinned copper braided shield
Optical shield covering	85 %
External sheath, color	black RAL 9005
External cable diameter D	7.7 mm ± 0.2 mm
Smallest bending radius, fixed installation	38.5 mm
Smallest bending radius, movable installation	77 mm
Cable weight	85 kg/km
Outer sheath, material	PVC
Material, filler	PVC
Material conductor insulation	PVC
Conductor material	Bare Cu litz wires
Insulation resistance	$\geq 10 \text{ G}\Omega \cdot \text{km}$
Conductor resistance	$\leq 78 \Omega / \text{km}$
Nominal voltage, cable	300 V
Test voltage, cable	3000 V
Ambient temperature (operation)	-25 °C ... 105 °C (cable, fixed installation)

Classifications

eCl@ss

eCl@ss 4.0	27060306
eCl@ss 4.1	27060306
eCl@ss 5.0	27061801
eCl@ss 5.1	27061801
eCl@ss 6.0	27061801
eCl@ss 7.0	27061801
eCl@ss 8.0	27062011
eCl@ss 9.0	27062011

ETIM

ETIM 3.0	EC001855
ETIM 4.0	EC001855
ETIM 5.0	EC001578

UNSPSC

UNSPSC 6.01	31251501
-------------	----------

Cable ring - SAC-8P-100,0-PVC/SH-0,25 - 1550708

Classifications

UNSPSC

UNSPSC 7.0901	31251501
UNSPSC 11	31251501
UNSPSC 12.01	31251501
UNSPSC 13.2	31251501

Approvals

Approvals

Approvals

UL Listed / cUL Listed / EAC / cULus Listed

Ex Approvals

Approvals submitted

Approval details

UL Listed 	
Nominal current IN	2 A
Nominal voltage UN	30 V

cUL Listed 	
Nominal current IN	2 A
Nominal voltage UN	30 V

EAC	
-----	--

Cable ring - SAC-8P-100,0-PVC/SH-0,25 - 1550708

Approvals

cULus Listed 

Accessories

Accessories

Stripping tool

Stripping tool - WIREFOX SAC - 1212623



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1550708](#)