

## ANNA-40-5-W

~30° wide beam with 5 optics

### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 40.0 mm
Height	10.7 mm
Fastening	glue, pin
ROHS compliant	yes 




### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
ANNA-40-5-W	Multi-lens	PMMA	clear	

### ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C11715_ANNA-40-5-W	760	120	40	6.9
» Box size:				



See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

## PHOTOMETRIC DATA (MEASURED):

### CREE

LED XB-D  
FWHM 29.0°  
Efficiency 85 %  
Peak intensity 2.2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:

### CREE

LED XP-E  
FWHM 36.0°  
Efficiency 87 %  
Peak intensity 1.6 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:

### CREE

LED XP-G  
FWHM 36.0°  
Efficiency 87 %  
Peak intensity 2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:

### LUMILEDS

LED LUXEON A  
FWHM 34.0°  
Efficiency 82 %  
Peak intensity 1.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:

## PHOTOMETRIC DATA (MEASURED):

### LUMILEDS

LED LUXEON Rebel

FWHM 30.0°

Efficiency 86 %

Peak intensity 1.9 cd/lm

LEDs/each optic 1

Light colour White

Required components:

### LUMILEDS

LED LUXEON Rebel ES

FWHM 29.0°

Efficiency 86 %

Peak intensity 2.2 cd/lm

LEDs/each optic 1

Light colour White

Required components:

### NICHIA

LED NCSxx19A

FWHM 28.0°

Efficiency 86 %

Peak intensity 2 cd/lm

LEDs/each optic 1

Light colour White

Required components:

### NICHIA

LED NVSxx19A

FWHM 33.0°

Efficiency 86 %

Peak intensity 1.5 cd/lm

LEDs/each optic 1

Light colour White

Required components:

## PHOTOMETRIC DATA (MEASURED):

### OSRAM

Opto Semiconductors

LED Duris S5 (2 chip)

FWHM 26.0°


Efficiency 88 %

Peak intensity 2.9 cd/lm

LEDs/each optic 1

Light colour White

Required components:



### OSRAM

Opto Semiconductors

LED OSLON SSL 150

FWHM 34.0°

Efficiency 87 %

Peak intensity 2.4 cd/lm

LEDs/each optic 1

Light colour White

Required components:

### OSRAM

Opto Semiconductors

LED OSLON SSL 80

FWHM 26.0°

Efficiency 87 %

Peak intensity 2.4 cd/lm

LEDs/each optic 1

Light colour White

Required components:

## GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

## MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

## PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

**LEDiL Oy**  
Joensuunkatu 13  
FI-24240 SALO  
Finland

**LEDiL Inc.**  
228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

**Ledil Optics Technology  
(Shenzhen) Co., Ltd.**  
# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

**Local sales and technical  
support**  
[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

**Shipping locations**  
Salo, Finland  
Hong Kong, China

**Distribution Partners**  
[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)